Index

Symbols

.c, 12
.c file, 59
.h, 12
.make, 12
_stubs.c, 2, 11, 14, 60, 61
    callback templates, 57
    callbacks, 57
    merging, 51
_stubs.c.BAK, 14, 60, 61
_stubs.c.delta, 14, 60, 61
_ui.c, 2, 11
    description, 54
_ui.h, 2, 11
    description, 56, 57

A

about this book
    font conventions, xvi
    prerequisite reading, xiii
Action Menu items, 49
Adjust, 48, 49
AnyEvent, 48, 49
ArgList, 54

B

background reading, xv
base window
    creating, 24
bin subdirectory, 89
building
    the interface, 23

C

C declarations, 59
callbacks, 57
    arguments, 58
    removing, 61
    setting up in Devguide, 60
    templates, 57
callData (callback argument), 58
CallFunction, 35, 48, 49
    templates, 58
clientData (callback argument), 58
command line options, 51
compiling source code, 12, 46, 76
connections
    Action menu items, 49
    CallFunction, 35
    changing actions for, 60
    changing names of, 61

removing, 61
setting up in Devguide, 7, 16, 35, 47, 60
When menu items, 48
Connections Manager, 7, 16, 47
control areas
layered, 37
Create, 48
create procs, 3, 70
setting up in Devguide, 50
using for glyphs, 81
using for icons, 79
creating
base windows, 24
the interface, 23

D

demo subdirectory, 89
Destroy, 48, 49
Devguide
background on, 1
configuring for GOLIT, 6
designing interfaces for GOLIT, 6
features not supported by GOLIT, 91
files included with, 89
installing, 2
interacting with, 2
meaning of name, 2
setting up create procs, 50
test mode, 39
Disable, 49
doc subdirectory, 90
documentation, 90
Done, 48, 49
DoubleClick, 48, 49
drag and drop, 92
drop sites, 92
DroppedUpon, 48, 49

E

Enable, 49
Enter, 48, 49
ExecuteCode, 48, 49
Exit, 48, 49

F

fallback resources, 57
files, 52, 59
fonts, using Create Procs to set, 73
functions
common to more than one `.G` file, 59

G

generated files, 3, 11, 52
_stubs.c, 57
_stubs.c.BAK, 60
_stubs.c.delta, 60
_ui.c, 54
Makefile, 58
overview, 53
project_name.c, 59
project_name.C.BAK, 61
project_name.c.BAK
project_name.c.BAK, 61
project_name.c.delta, 61
project_name.h, 59
project_name.h.BAK, 61
project_name.make, 60
ui.h, 56
generating code, 40
GetLabel, 49
GetValueNumber, 50
GIL (Graphical Interface Language) files, 47
glyphs, 92
using for labels, 81
GOLIT
background on, 3
definition of, 1
generated files, 52
generated files overview, 53
getting started, 5
how to use it, 50
interacting with, 2

golit (command), 8
    options, 51
    using options
        -? (help), 51
        -n (nomerge), 51
golit command
    using options
        -s (silent), 52
`golit` command
    using options
        `-m (-main)`, 51
        `-p`, 51
golit(command)
    using options
        -i, 51
        -k (kandr), 51
        -r (resources), 52
GolitFetchLastWidgetID(), 62
GolitFetchWidgetHier(), 67
GolitNameToWidget(), 13, 62
GUIDEHOME, 2, 77

H

Help, 92
help, 92
    using Create Procs to register, 70
Hide, 50
home directories, 2, 77
how to use GOLIT, 50

I

icons, 92
    using create procs to specify, 79
If, 60
include subdirectory, 89
included files, 89
instance name, 63
instantiating widgets, 66
integrating interface and application code, 61
interface
    building, 23
internationalization, 92

K

KeyPress, 49
Keypress, 48

L

label images, 81
labels
    fonts, 91
layered panes, 37
lib subdirectory, 90
libgolit functions, 66
libgolit.h, 89
libgolitI.h, 89
libraries, 90
LoadTextfile, 50

M

`main()` function, 59
Makefile, 11, 58
    parameters, 58
man pages, 90
man subdirectory, 90
MANPATH, 90
manual
    GOLIT Reference, xiv
    libgolit reference, xiv
    Unsupported Devguide features, xiv
Menu, 48, 49

N

Notify, 48, 49
numeric text fields, 92

O

OPEN LOOK, 3
    recommendations, 23

OPEN LOOK Style Guide, 23
OpenWindows Developer's Guide
    meaning of name, 2
OPENWINHOME, 2, 77
options (command line)
    ? (help), 51
    m (main), 51
    -n (no merge), 51
    -p (project), 51
    -s (silent), 52

P

Popdown, 48, 49
Popup, 48, 49
printf(), 58, 61
PROGRAM parameter, 58
project files, 59
project_name.c, 59
project_name.C.BAK, 61
project_name.c.delta, 61
project_name.h, 59
project_name.h.BAK, 61
project_name.make, 60

R

recommended reading, xv
references, xv
regenerating user interface code, 14
Repaint, 48, 49
Resize, 48, 49
resize corners, 33
resources
    fallback, 57
    setting programmatically, 62

S

scrolling lists, 92
Select, 48, 49
SetLabel, 50
setting stack, 92
SetValueNumber, 50
Show, 50
siblings, 54, 55
source code
    compiling, 46, 76
SOURCES.c parameter, 58
SOURCES.G parameter, 59
SOURCES.h parameter, 58
src subdirectory, 90
suffixes
    .BAK, 60
    .c, 2
    .delta, 60
    .G, 2
    .h, 2
    .P, 5
    make, 12

T

term panes, 92
test mode, 39
text fields, 63
    numeric, 92
    setting to read only, 81

U

Unselect, 48, 49
user interface (UI) code, 2
    regenerating, 14, 60
user's manual
    getting started, xiv
    GOLIT reference, xiv
    libgolit reference, xiv
    Unsupported Devguide features, xiv

W

When, 48
    menu items, 48
widget description pointer, 54, 63
widget descriptor, 54, 63
widget hierarchy, 54

widget tree
    instantiating parts of, 66
widgets
    getting ids for, 13, 62
    GOLIT names for, 54, 63
    setting resources, 62
    siblings, 54, 55

X

XtNconsumeEvent, 49
XtNdestroyCallback, 49
XtNdndTriggerCallback, 49
XtNpopdownCallback, 49
XtNpopupCallback, 49
XtNresizeCallback, 49
XtNselect, 49
XtNsliderMover, 49
XtNunselect, 49
XtNverification, 49