Index

Symbols

.c, 7
.c file, 19
.h, 7
.make, 7
_stubs.c, 3, 7, 9, 21
    callback templates, 18
    callbacks, 18
    merging, 13
_stubs.c.BAK, 9, 21
_stubs.c.delta, 9, 21
_ui.c, 3, 7
    description, 15
_ui.h, 3, 7
    description, 17, 18

A

about this book
    font conventions, xiii to xiv
    prerequisite reading, xii
Action Menu items, 12
Adjust, 11
AnyEvent, 11
As, 22

B

bin subdirectory, 33

C

C declarations, 20
callbacks, 18
    arguments, 18
    removing, 21
    setting up in Devguide, 20
    templates, 18
callData (callback argument), 18
CallFunction, 12
    templates, 18
clientData (callback argument), 18
command line options, 13
compiling source code, 8
connections
    Action menu items, 12
    changing actions for, 20
    changing names of, 21
    removing, 21
    setting up in Devguide, 20

D

Destroy, 11
Devguide

background on, 1
features not supported by GMF, 35
files included with, 33
interacting with, 3
meaning of name, 1
Disable, 12
Done, 11
DoubleClick, 11
drag and drop, 36
drop sites, 36
DroppedUpon, 11

E

Enable, 12
Enter, 11
ExecuteCode, 12
Exit, 11

F

files, 14, 19
functions
common to more than one `.G` file, 20

G

generated files, 3, 7, 14
_stubs.c, 18
_stubs.c.BAK, 21
_stubs.c.delta, 21
_ui.c, 15
Makefile, 19
overview, 15
project_name.c, 19
project_name.C.BAK, 21
project_name.c.BAK
project_name.c.BAK, 21
project_name.c.delta, 21
project_name.h, 20
project_name.h.BAK, 21
project_name.make, 20
ui.h, 17
GetLabel, 12
GetValueNumber, 12
GMF
generated files, 14
generated files overview, 15
getting started, 5
how to use it, 12
interacting with, 3
gmf (command)
options, 13
using options
-? (help), 13
-k (kandr), 13
-n (nomerge), 13
-r (resources), 13
gmf command
using options
-s (silent), 14
`gmf` command
using options
`-m (-main)`, 13
`-p`, 13
GUIDEHOME, 25
GUIL
how to use it, 31
guil (command)
using options
-? (help), 32
-f (force), 32
guil command
using options
-s (silent), 32
`guil` command
using options
`-p`, 32

H

Help, 35
help, 35
Hide, 12
home directories, 25
how to use GMF, 12
how to use GUIL, 31

I

icons, 36
If, 21
include subdirectory, 33
included files, 33
instance name, 23
integrating interface and application code, 22
internationalization, 35

L

labels
  fonts, 35
lib subdirectory, 33
libgmf.h, 33
libraries, 33
LoadTextfile, 12

M

`main()` function, 19
Makefile, 7, 19
  parameters, 19
man pages, 34
man subdirectory, 34
MANPATH, 34
manual
  GMF Reference, xii
  Unsupported Devguide features, xii
MOTIFHOME, 25

N

numeric text fields, 36

O

OpenWindows Developer's Guide
  meaning of name, 1
options (command line)
  ? (help), 13, 32
  m (main), 13
  -n (no merge), 13
  -p (project), 13, 32
  -s (silent), 14, 32

P

printf(), 18, 22
PROGRAM parameter, 19
project files, 19
project_name.c, 19
project_name.C.BAK, 21
project_name.c.delta, 21
project_name.h, 20
project_name.h.BAK, 21
project_name.make, 20

R

resources
  setting programmatically, 22

S

SetLabel, 12
SetValueNumber, 12
Show, 12
SOURCES.c parameter, 19
SOURCES.G parameter, 19
SOURCES.h parameter, 19
src subdirectory, 34
suffixes
  .BAK, 21
  .c, 3
  .delta, 21
  .G, 3
  .h, 3
  make, 7

T

term panes, 36
text fields, 22
  numeric, 36

U

user interface (UI) code, 1
    regenerating, 21
user's manual
    GMF reference, xii
    Unsupported Devguide features, xii

W

When, 22
widget hierarchy, 16
widgets
    GMF names for, 23
    setting resources, 22

X

XtNdestroyCallback, 11
XtNpopdownCallback, 11
XtNpopupCallback, 12
XtNresizeCallback, 12
XtNselect, 11
XtNsliderMover, 11
XtNunselect, 12
XtNverification, 11