Index

Symbols

" (quotation marks)
    BNF notation, 186
    XFN composite name syntax, 159
    XFN standard syntax model, 157
* in BNF notation, 186
+ in BNF notation, 186
. (dots)
    ... namespace identifier, 61, 62
    /... namespace identifier, 62
    trailing, in organization names, 31, 38
/ (slashes)
    /... namespace identifier, 62
    double slashes in organization names, 45, 99
    FNS component separator, 42
    in service names, 39
    trailing, in organization names, 100
    XFN component separator, 157, 159 to 161
::= in BNF notation, 186
\ as XFN component escape character, 159
_ (underscore)
    in namespace identifiers, 41, 56
    in XFN terminology, 42
{} (curly braces) in BNF notation, 186
| (pipe) in BNF notation, 186
’ (single quote) in XFN composite name syntax, 159

Numerics

0 value, 135

A

abstract data types, 134
access control
    `attribute no permission` message, 101
    changing, 99
    checking, 98 to 99
    `no permission` message, 103, 105 to 106
addresses
    mail destinations, 33
    multiple, 11
    NIS+ root reference, 111 to 112
    `no supported address` message, 103
    properties, 12
    references, 11 to 12
    XFN interface parameters, 153 to 154

- administration
  - federating NIS+ with global naming systems, 111 to ??
    - obtaining NIS+ root reference, 111 to 112
    - under DNS, 112 to ??
    - under X.500, 114 to ??
  - file system namespace, 117 to 126
    - automounter, 119 to 120
    - file context administration, 126
    - file context creation, 120 to 126
    - NFS file servers, 118 to 119
    - overview, 117 to 120
  - FNS on NIS+, 69 to 109
    - access control checking, 98 to 99
    - browsing FNS structures using NIS+ commands, 97
    - error messages, 100 to 104
    - FNS attribute management, 92 to 94
    - FNS context creation, 73 to 83
    - FNS context management, 83 to 92, 141 to 142
    - maintaining consistency between NIS+ and FNS, 94 to 96
    - mapping FNS contexts to NIS+ objects, 96
    - replicating FNS service, 72
    - resource requirements, 70
    - setting up FNS namespace, 71 to 72
    - setting up NIS+ service for FNS, 70 to 71
    - troubleshooting, 104 to 109
  - printer namespace, 127 to 130
    - overview, 127
    - using files, 128
    - using NIS, 129
    - using NIS+, 129 to 130
- alias host names, 77
- all hosts context
  - creating, 74, 76
  - troubleshooting creation, 107
- all users context
  - creating, 74, 77
  - troubleshooting creation, 107
- API usage model, 22
- application programming
  - namespace browser example, 168 to 177
    - code, 168 to 175
    - commands, 175
    - diagram, 168
    - sample output, 176 to 177
  - printer example, 178 to 183
    - client, 179 to 181
    - server, 181 to 183
  - XFN composite names, 159 to 166
    - naming system boundaries and component separators, 161 to 163
    - resolution, 163 to 166
    - syntax, 159 to 161
  - XFN interfaces, 133 to 158
    - *See also* client programming interfaces
    - abstract data types, 134
    - base attribute interface, 143 to 149
    - base context interface, 135 to 143
    - conventions, 134
    - memory management policies, 135
    - overview, 133 to 135
    - parameters, 153 to 155
    - parsing compound names, 156 to 158
    - status codes, 150 to 153
    - status objects, 137, 145, 150
    - usage, 134
- applications
  - API usage model, 22
  - DeskSet tools, 32 to 35
  - FNS implementation, 10
  - FNS interaction, 19 to 21
  - name services, 26, 27

architectural model, 11 to 16
attributes, 13
composite names, 15 to 16
compound names, 13 to 14
contexts, 12
initial context, 16
references, 11 to 12
XFN links, 15
ASCII string XFN identifier format, 154
asterisk (*) in BNF notation, 186
atomic names
See also namespace identifiers
in compound names, 13
in contexts, 12
global level, 62
initial context bindings for global naming, 62
namespace identifiers in the enterprise, 41 to 42
`attribute no permission` message, 101
attribute operations
See also base attribute interface; context operations
attribute-modification operations, 146
get attribute, 145 to 146
get attribute identifiers, 148
get attribute values, 147
get multiple attributes, 148 to 149
modify attribute, 146
modify multiple attributes, 149
multiple-attribute operations, 147 to 149
relationship to naming operations, 144 to 145
single-attribute operations, 145 to 147
status objects, 145
XFN attribute model, 143 to 144
`attribute value required` message, 101
attribute-modification lists, 155
attributes
adding attributes or values, 92, 93, 146
base attribute interface, 143 to 149
attribute-modification operations, 146
multiple-attribute operations, 147 to 149
relationship to naming operations, 144 to 145
single-attribute operations, 145 to 147
status objects, 145
supporting interfaces, 133 to 134
XFN attribute model, 143 to 144
deleting attributes or values, 93
described, 13
error messages, 101, 102, 103, 104
getting, 145 to 146
identifiers, 148
multiple attributes, 148 to 149
syntax attributes of context, 143
values, 147
listing, 93
managing and examining, 92 to 94
modifying values, 94
replacing, 93
sets, 155
syntax attributes, 156, 158
getting, 143
X.500 attribute syntax for XFN references, 195 to 199
XFN interface parameters, 155
XFN model, 143 to 144
`authentication failure` message, 101
automounter, 119 to 120
multiple locations, 124
variable substitution, 125

B

backslash (\) as XFN component escape character, 159
Backus-Naur Form (BNF), 186 to 187
`bad reference` message, 101
base attribute interface, 143 to 149
  See also client programming interfaces
  abstract data types, 134
  attribute-modification operations, 146
  conventions, 134
  memory management policies, 135
  multiple-attribute operations, 147 to 149
  parameters, 153 to 155
    attribute modification lists, 155
    attribute sets, 155
    attributes and attribute values, 155
    composite names, 153
    identifiers, 154
    references and addresses, 153 to 154
    strings, 155
  parsing compound names, 156 to 158
    syntax attributes, 156, 158
    XFN standard syntax model, 156 to 157
  relationship to naming operations, 144 to 145
  single-attribute operations, 145 to 147
  status objects, 145
  supporting interfaces, 133 to 134
  usage, 134
  XFN attribute model, 143 to 144
base context interface, 135 to 143
  See also client programming interfaces
  abstract data types, 134
  context handles, 137
  conventions, 134
  lookup and list contexts, 138 to 140
  managing contexts, 141 to 142
  memory management policies, 135
  names in context operations, 136
  other context operations, 142 to 143
  parameters, 153 to 155
    attribute modification lists, 155
    attribute sets, 155
    attributes and attribute values, 155
    composite names, 153
    identifiers, 154
    references and addresses, 153 to 154
    strings, 155
  parsing compound names, 156 to 158
    syntax attributes, 156, 158
    XFN standard syntax model, 156 to 157
  requirements for operations, 136 to 137
  status objects, 137
  supporting interfaces, 133 to 134
  updating bindings, 140 to 141
  usage, 134
begin quote (") in XFN standard syntax model, 157
  See also double quotes
bind/lookup model, 22
bindings
  access control
    changing, 99
    checking, 98 to 99
  adding, 140
  calendar service example, 33
  composite names to references, 89 to 91, 108
  displaying, 83 to 84
  initial context bindings for enterprise naming, 54 to 60
    example, 54
    host-related bindings, 58 to 59
    "shorthand" bindings, 59 to 60
    table, 55
    user-related bindings, 56 to 57
  initial context bindings for global naming, 62

listing names and bindings in contexts, 139
printers, 127
removing
composite names, 91, 108
terminal atomic name, 140 to 141
renaming, 91, 141
updating, 140 to 141
BNF (Backus-Naur Form), 186 to 187
boundaries (naming system) and component separators, 161 to 163
strong separation, 161 to 162
weak separation, 162 to 163
browsing
See also displaying; listing; lookup operations
FNS structures using NIS+ commands, 97
namespace browser programming example, 168 to 177
code, 168 to 175
commands, 175
diagram, 168
sample output, 176 to 177

C

Calendar Manager
calendar service example, 33 to 35
FNS policies, 32, 33 to 35
"Cannot obtain initial context" message, 104
canonical namespace identifiers, 42, 56
checking access control, 98 to 99
client programming interfaces, 133 to 158
See also application programming
abstract data types, 134
base attribute interface, 143 to 149
attribute-modification operations, 146
multiple-attribute operations, 147 to 149
relationship to naming operations, 144 to 145
single-attribute operations, 145 to 147
status objects, 145
XFN attribute model, 143 to 144
base context interface, 135 to 143
context handles, 137
lookup and list contexts, 138 to 140
managing contexts, 141 to 142
names in context operations, 136
other context operations, 142 to 143
requirements for operations, 136 to 137
status objects, 137
updating bindings, 140 to 141
conventions, 134
memory management policies, 135
overview, 133 to 135
parameters, 153 to 155
attribute modification lists, 155
attribute sets, 155
attributes and attribute values, 155
composite names, 153
identifiers, 154
references and addresses, 153 to 154
strings, 155
parsing compound names, 156 to 158
syntax attributes, 156, 158
XFN standard syntax model, 156 to 157
status codes, 150 to 153
status objects, 150
base attribute interface, 145
base context interface, 137
supporting interfaces, 133 to 134
usage, 134
`cm` service, 33 to 35
code sets incompatible, 102
codes
attribute-modification operation, 146
link status, 150
status, 150 to 153

commands
See also attribute operations; context operations; *specific commands, functions, and operations*
browsing FNS structures using NIS+ commands, 97
`fnbrowse` program, 175
FNS context management, 83 to 92
XFN interface function names, 134
`communication failure` message, 101
component separator (/)
FNS components, 42
naming system boundaries and, 161 to 163
strong separation, 161 to 162
weak separation, 162 to 163
XFN composite name syntax, 159 to 161
XFN standard syntax model, 157
composing XFN composite name strings, 189 to 190
composite names
applications' use of FNS, 10
binding to references, 89 to 91, 108
defined, 4, 15
destroying named objects, 92, 109
displaying bindings, 83 to 84
examples
calendar service, 33 to 35
hosts, 30
illustration, 16
organizations, 29
sites, 30
user, 29
host naming systems, 30
need for uniform policy, 6 to 7
organization naming systems, 29
parsing XFN composite names, 187 to 189
removing from namespace, 91 to 92, 108 to 109
resolution, 163 to 166
coexistence of explicit and implicit NNSPs, 165
explicit NNSPs, 163 to 164
implicit NNSPs, 164 to 165
XFN links, 165
site naming systems, 30
user naming systems, 29
XFN composite names, 159 to 166
naming system boundaries and component separators, 161 to 163
resolution, 163 to 166
syntax, 159 to 161, 185 to 190
XFN context implementation, 136
XFN interface parameters, 153
XFN syntax, 159 to 161, 185 to 190
Backus-Naur Form (BNF), 186 to 187
composing the composite name string, 189 to 190
decomposing the composite name string, 187 to 189
encoding, 185
string and structural forms, 160 to 161
compound names, 13 to 14
described, 13
hierarchical naming system examples, 13 to 14
parsing, 156 to 158
syntax attributes, 156, 158
XFN standard syntax model, 156 to 157
`configuration error` message, 101
`const` parameters, 135
`const` pointers, 135
constants, XFN interface conventions, 134
`context not empty` message, 102

context operations
See also attribute operations; base context interface
bind, 140
construct context handle from reference, 137
construct handle to initial context, 137
context handles, 137
create subcontext, 141 to 142
destroy context handle, 143
destroy subcontext, 142
get reference to context, 142
get syntax attributes of context, 143
list bindings, 139
list names, 138 to 139
lookup, 138
lookup link, 139 to 140
managing contexts, 141 to 142
names in, 136
rename, 141
requirements, 136 to 137
status objects, 137
unbind, 140 to 141
updating bindings, 140 to 141
context shared object modules, 20
contexts
See also bindings; initial context; parent contexts; subordinate contexts
base context interface, 135 to 143
context handles, 137
lookup and list contexts, 138 to 140
managing contexts, 141 to 142
names in context operations, 136
other context operations, 142 to 143
requirements for operations, 136 to 137
status objects, 137
supporting interfaces, 133 to 134
updating bindings, 140 to 141
changing ownership, 99
checking naming inconsistencies, 95 to 96
`context not empty` message, 102
creating individually
all hosts context, 74, 76, 107
all users context, 74, 77, 107
debugging, 74
file context, 82
`fncreate` command overview, 73 to 74
generic context, 74, 80 to 81
namespace identifier context, 74, 82
organization context, 75
printer context, 80
service context, 79 to 80
single host context, 76, 107
single user context, 78 to 79, 107
site context, 81
creating subcontexts, 141 to 142
defined, 12
destroying
handles, 143
subcontexts, 142
displaying the binding, 83 to 84
enterprise root, 45 to 46
files, 52
administering, 126
creating, 120 to 126
getting
handles, 137
references, 142
syntax attributes, 143
hosts, 50 to 51
initial context
bindings for enterprise naming, 54 to 60
calendar service example, 34
described, 16
listing contents, 85 to 88
managing and examining, 83 to 92, 141 to 142
mapping to NIS+ objects, 96
`not a context` message, 104
organizational units, 46 to 47
principles, 7 to 8

printers, 53, 128 to 130
services, 51 to 52
sites, 47 to 49
syntax-related attributes, 156
tree structure, 13 to 14
troubleshooting
cannot create host- or user-related contexts, 107
cannot remove context, 107
checking naming inconsistencies, 95 to 96
debugging creation, 74
users, 49
XFN contexts, 12
`continue operation using status values` message, 102
`ctx_dir` directory
checkpointing, 72
creating, 71
replicating, 72
verifying creation, 71
curly braces in BNF notation, 186
customized namespace identifiers, 42, 56

D

`-D`, `fncreate` option, 74
`-d`, `fnattr` option, 93
data types
abstract data types, 134
XFN interface conventions, 134
debugging context creation, 74
decomposing XFN composite name strings, 187 to 189
deleting, *See* removing
DeskSet tools, 32 to 35
destroying
See also removing
context handles, 143
named objects, 92
context not removed, 107
"operation failed" not returned, 109
subcontexts, 142
DIB (directory information base), 63 to 64
directories
automounter, 119 to 120
NIS+ master server, 71
directory information base (DIB), 63 to 64
disk-space requirements for FNS on NIS+, 70
displaying
See also listing; lookup operations
access control, 98 to 99
bindings, 83 to 84
browsing FNS structures using NIS+ commands, 97
DNS table, editing, 112 to ??
DNS, *See* Domain Name System (DNS)
Domain Name System (DNS)
as nonterminal name system, 63
described, 9
federating, 62 to 63
federating NIS+ under, 112 to ??
FNS implementation, 9
hierarchical naming system, 13
name resolution, 62
text record format for XFN references, 191 to 194
domains (NIS+) and FNS organizational units, 30 to 31
dots (.)
... namespace identifier, 61, 62
/... namespace identifier, 62
trailing, in organization names, 31, 38
double quotes
BNF notation, 186
XFN composite name syntax, 159
XFN standard syntax model, 157

E

editing the DNS table, 112 to ??
encoding for XFN composite names, 185
end quote (") in XFN standard syntax model, 157
See also double quotes
enterprise level of service, 26, 27

enterprise namespace policies, 37 to 60
arrangement of objects, 28
file namespace, 40
host namespace, 39
illustrated, 27
initial context bindings, 54 to 60
example, 54
host-related bindings, 58 to 59
"shorthand" bindings, 59 to 60
table, 55
user-related bindings, 56 to 57
namespace identifiers, 41 to 42
namespace structure, 42 to 54
enterprise root, 45 to 46
example, 44
files, 52
hosts, 50 to 51
organizational units, 46 to 47
printers, 53
services, 51 to 52
sites, 47 to 49
users, 49
organizational unit namespace, 38
printer namespace, 40
service namespace, 39 to 40
site namespace, 38
table of policies, 43
user namespace, 39
enterprise root context, 45 to 46
enumeration handle invalid, 102
erasing, *See* removing
`error` message, 102
error messages, 100 to 104
See also troubleshooting
`attribute no permission`, 101
`attribute value required`, 101
`authentication failure`, 101
`bad reference`, 101
"Cannot obtain initial context", 104
`communication failure`, 101
`configuration error`, 101
`context not empty`, 102
`continue operation using status values`, 102
`error`, 102
`illegal name`, 102
`incompatible code sets`, 102
`insufficient resources`, 102
`invalid attribute identifier`, 102
`invalid attribute value`, 102
`invalid enumeration handle`, 102
`invalid syntax attributes`, 103
`link error`, 103
`link loop limit reached`, 103
`malformed link`, 103
`name in use`, 103, 108
`name not found`, 103
`no permission`, 103, 105 to 106
`no such attribute`, 103
`no supported address`, 103
`not a context`, 104
`operation not supported`, 104
overview, 100
`partial result returned`, 104
status codes, 151 to 153
`success`, 104
`syntax not supported`, 104
`too many attribute values`, 104
`unavailable`, 104
examining, *See* displaying; listing; lookup operations
explicit NNSPs, 163 to 164
See also next naming system pointers (NNSPs)
exporting the FNS interface, 10

F

`-f`, `fncreate` option
all hosts context, 76
all users context, 78
overview, 74
federated enterprise namespace policies, *See* enterprise namespace policies
federated global namespace policies, *See* global namespace policies

Federated Naming Service
API usage model, 22
application view, 19 to 21
architectural model, 11 to 16
browsing FNS structures using NIS+ commands, 97
described, xvii, 4
error messages, 100 to 104
file system view, 18
need for, 5 to 8
coherence in naming, 7 to 8
name composition uniformity, 6 to 7
naming interface uniformity, 5 to 6
principles for policies, 7 to 8
registry of service names, 40
setting up
FNS namespace setup, 71 to 72
NIS+ service setup, 70 to 71
replicating FNS service, 72
resource requirements, 70
Solaris environment, 8 to 10
user's view, 17 to 18
XFN compliance, xvii, 5
XFN vs., 5
federating
DNS, 62 to 63
NIS+ with global naming systems, 111 to ??
obtaining NIS+ root reference, 111 to 112
under DNS, 112 to ??
under X.500, 114 to ??
X.500, 63 to 65
File Manager, 32
files and file systems
contexts, 52
creating, 82
ownership, 82
enterprise namespace, 40
enterprise namespace policies, 43
as enterprise policy entities, 28
FNS interaction, 18
FNS policies, 32
FNS-based naming, 9
input file for `fncreate_fs(1M)`
alternate format, 125
creating, 121 to 123
namespace administration, 117 to 126
automounter, 119 to 120
file context administration, 126
file context creation, 120 to 126
NFS file servers, 118 to 119
overview, 117 to 120
namespace identifier, 41
NFS file servers, 118 to 119
`printer` context administration, 128
`FN_` prefix, 134
`fn_` prefix, 134
`fn_attr_get()` function, 145 to 146, 147
`fn_attr_get_ids()` function, 148
`fn_attr_get_values()` function, 146, 147
`fn_attr_modify()` function, 146
`fn_attr_multi_modify()` function, 149
`fn_attr_multiget()` function, 148
`FN_ATTR_OP_ADD` operation code, 146
`FN_ATTR_OP_ADD_EXCLUSIVE` operation code, 146
`FN_ATTR_OP_ADD_VALUES` operation code, 146
`FN_ATTR_OP_REMOVE` operation code, 146
`FN_ATTR_OP_REMOVE_VALUES` operation code, 146
`fn_composite_name_from_string()` function, 187 to 189
`fn_ctx_bind()` function, 140
`fn_ctx_bindinglist_destroy()` function, 139
`fn_ctx_bindinglist_next()` function, 139
`fn_ctx_create_subcontext()` function, 141 to 142
`fn_ctx_destroy_subcontext()` function, 142

fn_ctx_get_ref() function, 142
fn_ctx_get_syntax_attrs() function, 143
fn_ctx_handle_destroy() function, 143
fn_ctx_handle_from_initial() function
  getting context handles, 137
  getting initial context object, 54
  host-related bindings, 58 to 59
  user-related bindings, 56 to 57
fn_ctx_handle_from_ref() function, 137
fn_ctx_list_names() function, 138
fn_ctx_listbindings() function, 139
fn_ctx_lookup() function
  support required, 136
  using, 138
fn_ctx_lookup_link() function, 139 to 140
fn_ctx_namelist_destroy() function, 138
fn_ctx_namelist_next() function, 138
fn_ctx_rename() function, 141
fn_ctx_unbind() function, 140 to 141
FN_E_ATTR_NO_PERMISSION status code, 151
FN_E_ATTR_VALUE_REQUIRED status code, 151
FN_E_AUTHENTICATION_FAILURE status code, 151
FN_E_COMMUNICATION_FAILURE status code, 151
FN_E_CONFIGURATION_ERROR status code, 151
FN_E_CONTINUE status code, 151
FN_E_CTX_NO_PERMISSION status code, 151
FN_E_CTX_NOT_EMPTY status code, 151
FN_E_CTX_UNAVAILABLE status code, 151
FN_E_ILLEGAL_NAME status code, 151, 157
FN_E_INCOMPATIBLE_CODE_SETS status code, 151, 157
FN_E_INSUFFICIENT_RESOURCES status code, 151
FN_E_INVALID_ATTR_VALUE status code, 152
FN_E_INVALID_ENUM_HANDLE status code, 152
FN_E_INVALID_SYNTAX_ATTRS status code, 152
FN_E_LINK_ERROR status code, 150, 152
FN_E_LINK_LOOP_LIMIT status code, 152
FN_E_MALFORMED_LINK status code, 152
FN_E_MALFORMED_REFERENCE status code, 152
FN_E_NAME_IN_USE status code, 152
FN_E_NAME_NOT_FOUND status code, 152
FN_E_NO_SUCH_ATTRIBUTE status code, 152
FN_E_NO_SUPPORTED_ADDRESS status code, 152
FN_E_NOT_A_CLIENT status code, 152
FN_E_OPERATION_NOT_SUPPORTED status code, 136, 152
FN_E_PARTIAL_RESULT status code, 152
FN_E_SYNTAX_NOT_SUPPORTED status code, 153
FN_E_TOO_MANY_ATTR_VALUES status code, 153
FN_E_UNSPECIFIED_ERROR status code, 153
FN_ID_DCE_UUID XFN identifier format, 154
FN_ID_ISO_OID_BER XFN identifier format, 154
FN_ID_ISO_OID_STRING XFN identifier format, 154
FN_ID_STRING XFN identifier format, 154

fn_multigetlist_destroy() function, 148 to 149
fn_multigetlist_next() function, 148 to 149
FN_status_t parameter, 137
fn_std_syntax_ava_separator XFN syntax attribute, 158
fn_std_syntax_begin_quote XFN syntax attribute, 158
fn_std_syntax_case_insensitive XFN syntax attribute, 158
fn_std_syntax_code_sets XFN syntax attribute, 158
fn_std_syntax_end_quote XFN syntax attribute, 158
fn_std_syntax_escape XFN syntax attribute, 158
fn_std_syntax_local_info XFN syntax attribute, 158
fn_std_syntax_separator XFN syntax attribute, 158
fn_std_syntax_typeval_separator XFN syntax attribute, 158
fn_string_from_composite_name() function, 189 to 190
FN_SUCCESS status code, 151
fn_syntax_direction XFN syntax attribute, 158
fn_syntax_type XFN syntax attribute, 158
fn_valuelist_destroy() function, 147
fn_valuelist_next() function, 147
fnattr command
  adding attributes, 92
  deleting attributes, 93
  listing attributes, 93
  modifying attribute values, 94
  other options, 93
  overview, 92
fnbind command
  binding composite names to references, 89 to 90
  name in use message with -s option, 108
  options, 89
  syntax, 83
fnbind -r command
  binding composite names to references, 90 to 91
  options, 89
  syntax, 83
fnbrowse program example, 168 to 177
  code, 168 to 175
  commands, 175
  diagram, 168
  sample output, 176 to 177
fncheck command, 95 to 96
fncreate command
  all hosts context creation, 74, 76, 107
  all users context creation, 74, 77, 107
  debugging context creation, 74
  file context creation, 82
  FNS namespace setup, 71 to 72
  generic context creation, 74, 80 to 81
  name in use message with -s option, 108
  namespace identifier context creation, 74, 82
  NIS_GROUP environment variable setting, 70
  options, 74
  organization context creation, 75
  overview, 73 to 74
  printer context creation, 80
  service context, 80
  service context creation, 79
  single host context creation, 76, 107
  single user context creation, 78 to 79, 107
  site context creation, 81
  syntax, 73
  troubleshooting host- or user-related context creation, 107

`fncreate_fs(1M)` command
command-line input, 123 to 126
input file
alternate format, 125
creating, 121 to 123
multiple locations, 124
options, 121
overview, 120 to 121
syntax, 120
variable substitution, 125
`fndestroy` command
context not removed, 107
destroying named objects, 92
"operation failed" not returned, 109
syntax, 83
`fnlist` command
doesn't list suborganizations, 106
initial context contains nothing, 105
listing context contents, 85 to 88
options, 85
syntax, 83
`fnlookup` command
displaying bindings, 83 to 84
options, 83
syntax, 83
`fnrename` command
renaming existing bindings, 91
syntax, 83
FNS, *See* Federated Naming Service
`fns_hosts` table, 97
`fns_rserver` creation, 72
`fnunbind` command
`name in use` message, 108
"operation failed" not returned, 109
removing composite names, 91
syntax, 83
Font> message, 102
`fs` context type, 82
See also files and file systems
`fs` or `_fs` namespace identifier
See also files and file systems
FNS policy, 43
resolution, 41
functions
See also specific functions
XFN interface conventions, 134

G

generic context creation, 74, 80 to 81
`generic` context type, 80 to 81
getting
attribute identifiers, 148
attribute values, 147
attributes, 145 to 146
context handles, 137
multiple attributes, 148 to 149
reference to context, 142
syntax attributes of context, 143
global level of service, 26, 27
global namespace policies, 61 to 65
federating DNS, 62 to 63
federating X.500, 63 to 65
global namespace, 61
illustrated, 27
initial context bindings, 62
table of policies, 61

H

handles
context handles
destroying, 143
getting, 137
overview, 135
hard-disk space requirements for FNS on NIS+, 70
hierarchical naming system
compound name examples, 13 to 14
enterprise namespace structure, 44 to 45
`host` context type, 76
`host` or `_host` namespace identifier
FNS policy, 43
initial context binding, 55
resolution, 41
"shorthand" binding, 59
`hostname` context type, 39, 76

host-related bindings, 58 to 59
hosts
  aliases, 77
  as enterprise policy entities, 28
  bindings for enterprise naming, 58 to 59
  composite name examples, 30
  context creation
    all hosts, 74, 76
    single host, 76
    troubleshooting, 107
  context ownership, 76, 77
  contexts, 50 to 51
  enterprise namespace, 39
  enterprise namespace policies, 43
  namespace identifier, 41
`hosts.org_dir` table, 32

I

identifiers
  namespace
    canonical vs. Solaris customized, 42, 56
    context creation, 74, 82
    enterprise level, 41 to 42, 55
    global level, 61
  XFN interface parameters, 154
`illegal name` message, 102
implicit NNSPs, 164 to 165
  See also next naming system pointers (NNSPs)
`incompatible code sets` message, 102
inconsistencies
  checking context naming inconsistencies, 95 to 96
initial context
  See also contexts
  bindings for enterprise naming, 54 to 60
    example, 54
    host-related bindings, 58 to 59
    "shorthand" bindings, 59 to 60
    table, 55
    user-related bindings, 56 to 57
  bindings for global naming, 62
  calendar service example, 34
  cannot obtain, 104
  contains nothing, 105
  described, 16
  handle construction operation, 137
input file for `fncreate_fs(1M)`
  alternate format, 125
  creating, 121 to 123
`insufficient resources` message, 102
interfaces for programming, *See* client programming interfaces
Internet DNS, *See* domain name system (DNS)
`invalid attribute identifier` message, 102
`invalid attribute value` message, 102
`invalid enumeration handle`, 102
`invalid syntax attributes` message, 103
ISO OID XFN identifier formats, 154

J

junctions, 163 to 164
  See also next naming system pointers (NNSPs)

L

`-L`
  `fnbind` option, 89, 90
  `fnlookup` option, 83
`-l`
  `fnattr` option, 93
  `fnlist` option, 85, 87 to 88
`link error` message, 103
`link loop limit reached` message, 103

links (XFN)
composite name resolution, 165
creating and binding, 89, 90
described, 15
displaying binding, 83
error messages, 103
lookup operation, 139 to 140
status object information, 150
XFN header file, 134
XFN library, 134
listing
See also displaying; lookup operations
attributes and their values, 93
browsing FNS structures using NIS+ commands, 97
context contents, 85 to 88
context naming inconsistencies, 95 to 96
DNS domain contents, 62
`fns_hosts` table contents, 97
initial context contains nothing, 105
names and bindings in contexts, 139
names bound in contexts, 138 to 139
namespace browser programming example, 168 to 177
code, 168 to 175
commands, 175
diagram, 168
sample output, 176 to 177
NIS+ objects used by FNS, 97
printing references used for binding, 89, 90
suborganizations not listed, 106
lookup model, 22
lookup operations
See also displaying; listing
calendar service example, 33
contexts, 138
XFN links, 139 to 140

M

`-m`, `fnattr` option, 94
Mail Tool, 33
`malformed link` message, 103
managing, *See* administration
mapping FNS contexts to NIS+ objects, 96
memory management policies for client interfaces, 135
messages, *See* error messages
modules, context shared object, 20
mounting directories, 119 to 120
multiple addresses, 11
multiple attributes
getting, 148 to 149
getting identifiers, 148
modifying, 149
`myens` or `_myens` namespace identifier
initial context binding, 55
user-related binding, 57
`myorgunit` or `_myorgunit` namespace identifier
initial context binding, 55
user-related binding, 57
`myself` or `_myself` namespace identifier
initial context binding, 55
user-related binding, 56

N

`name in use` message, 103
with `fnbind -s`, 108
with `fncreate -s`, 108
with `fnunbind`, 108
`name not found` message, 103
name resolution
context operation support requirements, 136 to 137
DNS names, 62
enterprise level namespace identifiers, 42
status object information, 150
X.500 names, 64 to 65
XFN composite names, 163 to 166
coexistence of explicit and implicit NNSPs, 165
explicit NNSPs, 163 to 164
implicit NNSPs, 164 to 165
XFN links, 165

name service (NS) resource records, 63
name services
  described, 3 to 4
  for `printer` context administration, 128 to 130
  functions, 3
  resource records, 63
namespace browser programming example, 168 to 177
  code, 168 to 175
  commands, 175
  diagram, 168
  sample output, 176 to 177
namespace identifiers
  canonical vs. Solaris customized, 42, 56
  context creation, 74, 82
  context ownership, 83
  enterprise level, 41 to 42
    initial context bindings, 55
  global level, 61
namespace policies, *See* policies
naming
  See also composite names; compound names; policies
  context name inconsistencies, checking, 95 to 96
  context operation names, 136
  XFN attribute operations and, 144 to 145
  XFN interface conventions, 134
naming system boundaries and component separators, 161 to 163
  strong separation, 161 to 162
  weak separation, 162 to 163
navigating, *See* browsing
next naming system pointers (NNSPs)
  X.500 name resolution, 64
  XFN composite name resolution
    coexistence of explicit and implicit NNSPs, 165
    explicit NNSPs, 163 to 164
    implicit NNSPs, 164 to 165
NIS+
  described, 8
  federating with global naming systems, 111 to ??
    obtaining NIS+ root reference, 111 to 112
    under DNS, 112 to ??
    under X.500, 114 to ??
  FNS administration, 69 to 109
    access control checking, 98 to 99
    browsing FNS structures using NIS+ commands, 97
    error messages, 100 to 104
    FNS attribute management, 92 to 94
    FNS context creation, 73 to 83
    FNS context management, 83 to 92
    maintaining consistency between NIS+ and FNS, 94 to 96
    mapping FNS contexts to NIS+ objects, 96
    replicating FNS service, 72
    resource requirements, 70
    setting up FNS namespace, 71 to 72
    setting up NIS+ service for FNS, 70 to 71
    troubleshooting, 104 to 109
  FNS implementation, 8
  FNS policies, 30 to 32
    NIS+ domains and FNS organizational units, 30 to 31
    NIS+ hosts and FNS hosts, 32
    NIS+ users and FNS users, 31
  `printer` context administration, 129 to 130
  root reference, 111 to 112
NIS, `printer` context administration, 129
`NIS_GROUP` environment variable, 70 to 71

`niscat` command
checking access control, 98 to 99
listing `fns_hosts` contents, 97
`nischgrp` command, 99
`nischmod` command, 99
`nischown` command, 99
`nisls` command
browsing FNS structures, 97
verifying `ctx_dir` creation, 71
`nismkdir` command
master server assignment, 71
replicating FNS service, 72
`nisping` command, 72
NNSPs, *See* next naming system pointers (NNSPs)
`no permission` message, 103, 105 to 106
`no such attribute` message, 103
`no supported address` message, 103
`not a context` message, 104
NS records, 63
`nsid` context type, 82
See also namespace identifiers

O

`-O`
`fnattr` option, 94
`fnbind` option, 89
`-o`, `fncreate` option
all users context, 77
organization context, 76
overview, 74
single user context, 78
objects
classes, 195 to 199
destroying named objects, 92, 107, 109
`operation not supported` message, 104
operations, *See* attribute operations; context operations; *specific operations*
`org` context type, 75
`org` namespace identifier
initial context binding, 55
"shorthand" binding, 59
organizational units
composite name examples, 29
contexts, 46 to 47
creating, 75
ownership, 76
described, 28
double slashes in organization names, 45, 99
enterprise namespace, 38
enterprise namespace policies, 43
`fnlist` doesn't list suborganizations, 106
namespace identifier, 41
NIS+ domains and, 30 to 31
trailing dot in organization names, 31, 38
trailing slash in organization names, 100
`orgunit` or `_orgunit` namespace identifier
FNS policy, 43
initial context binding, 55
resolution, 41
"shorthand" binding, 59
`orgunit//` namespace identifier, 45
OSF DCE UUID XFN identifier format, 154

P

parent contexts
See also contexts
of enterprise root, 45
of files, 52
of hosts, 50
of organizational units, 46
of printers, 53
of services, 51
of sites, 47 to 48
of users, 49

parsing
compound names, 156 to 158
syntax attributes, 156, 158
XFN standard syntax model, 156 to 157
XFN composite names, 187 to 189
`partial result returned` message, 104
`passwd.org_dir` table, 31
periods, *See* dots (.)
permissions
`attribute no permission` message, 101
changing, 99
checking, 98 to 99
`no permission` message, 103, 105 to 106
pipe character (|) in BNF notation, 186
plus sign (+) in BNF notation, 186
pointer types, 135
See also next naming system pointers (NNSPs)
policies, 25 to 35
enterprise namespace, 37 to 60
arrangement of objects, 28
file namespace, 40
host namespace, 39
illustrated, 27
initial context bindings, 54 to 60
namespace identifiers, 41 to 42
namespace structure, 42 to 54
organizational unit namespace, 38
printer namespace, 40
service namespace, 39 to 40
site namespace, 38
table of policies, 43
user namespace, 39
global namespace, 61 to 65
federating DNS, 62 to 63
federating X.500, 63 to 65
global namespace, 61
illustrated, 27
initial context bindings for global naming, 62
goals, 25
information not specified, 26
information specified, 26
levels of services, 26, 27
need for uniformity, 6 to 7
overview, 26 to 28
principles for, 7 to 8
target client applications, 32 to 35
predefined constants, 134
primary status code, 150
principles for FNS policies, 7 to 8
Print Tool, 32
`printer` context type
administration
using files, 128
using NIS, 129
using NIS+, 129 to 130
creation, 80
`printer` namespace identifier
FNS policy, 43
resolution, 41
printers
context administration
using files, 128
using NIS, 129
using NIS+, 129 to 130
context creation, 80
contexts, 53
enterprise namespace, 40
enterprise namespace policies, 43
FNS policies, 32
FNS-based naming, 9
namespace identifier, 41
programming example, 178 to 183
client, 179 to 181
server, 181 to 183

printing
See also listing
references used for binding, 89, 90
programming, *See* application programming; client programming interfaces

Q

quotation marks
BNF notation, 186
XFN composite name syntax, 159
XFN standard syntax model, 157

R

`-r`
`fncheck` option, 95, 96
`fncreate` option, 74
`fncreate_fs(1M)` option, 121
`-r`, `fnbind` option, 89
RAM, memory-management policies for client interfaces, 135
references
address properties, 12
`bad reference` message, 101
binding composite names to, 89 to 91, 108
defined, 11
DNS text record format for XFN references, 191 to 194
getting for contexts, 142
handle construction operation, 137
NIS+ root reference, 111 to 112
printing references used for binding, 89, 90
status object information, 150
X.500 attribute syntax for XFN references, 195 to 199
XFN interface parameters, 153 to 154
registering service names, 40
relative distinguished names, 13
removing
bindings, 140 to 141
cannot remove context, 107
composite names from namespace, 91 to 92, 108 to 109
deleting attributes or values, 93
destroying
context handles, 143
named objects, 92, 107, 109
subcontexts, 142
renaming bindings, 91, 141
replacing attributes or values, 93
replicating FNS service, 72
requirements for FNS on NIS+, 70
resolution, *See* name resolution
resolver library, 62
resources
`insufficient resources` message, 102
requirements, 70
root reference for NIS+, 111 to 112
RPC services, FNS policies, 33

S

`-s`
`fnattr` option, 93
`fnbind` option, 89, 108
`fncheck` option, 95
`fncreate` option, 74, 108
separator character (/)
FNS component separator, 42
naming system boundaries and, 161 to 163
strong separation, 161 to 162
weak separation, 162 to 163
XFN composite name syntax, 159 to 161
XFN standard syntax model, 157

servers
NFS file servers, 118 to 119
NIS+
directory, 71
requirements for FNS, 70
print server programming example, 181 to 183
`service` context type, 79 to 80
`service` or `_service` namespace identifier
FNS policy, 43
resolution, 41
services
See also printers
as enterprise policy entities, 28
context creation, 79 to 80
context ownership, 80
contexts, 51 to 52
enterprise namespace, 39 to 40
enterprise namespace policies, 43
levels, 26, 27
namespace identifier, 41
registering names, 40
sets of attributes, 155
setting up FNS
FNS namespace setup, 71 to 72
NIS+ service setup, 70 to 71
replicating FNS service, 72
resource requirements, 70
"shorthand" bindings, 59 to 60
single host context
creating, 76
troubleshooting creation, 107
single quote in XFN composite name syntax, 159
See also quotation marks
single user context
creating, 78 to 79
troubleshooting creation, 107
`site` context type, 81
`site` or `_site` namespace identifier
FNS policy, 43
initial context binding, 56
resolution, 41
"shorthand" binding, 60
sites
composite name examples, 30
context creation, 81
context ownership, 81
contexts, 47 to 49
enterprise namespace, 38
enterprise namespace policies, 43
as enterprise policy entities, 28
namespace identifier, 41
slash (/)
/... namespace identifier, 62
double slashes in organization names, 45, 99
FNS component separator, 42
in service names, 39
trailing, in organization names, 100
XFN component separator, 157, 159 to 161
Solaris
customized namespace identifiers, 42, 56
FNS implementation
applications, 10
DNS, 9
file naming, 9
NIS+, 8
printer naming, 9
X.500, 9
status codes, 150 to 153
link status, 150
status objects, 150
base attribute interface, 145
base context interface, 137
storage requirements for FNS on NIS+, 70

strings
composing XFN composite name strings, 189 to 190
decomposing XFN composite name strings, 187 to 189
XFN composite name syntax, 159 to 161
XFN identifier formats, 154
XFN interface parameters, 155
XFN standard syntax model, 157
subcontexts, *See* subordinate contexts
subordinate contexts
See also contexts
creating, 141 to 142
destroying, 142
of enterprise root, 45 to 46
of files, 53
of hosts, 50 to 51
of organizational units, 47
of printers, 54
of services, 52
of sites, 48
of users, 49
suborganizations not listed by `fnlist`, 106
`success` message, 104
`syntax not supported` message, 104

T

`-t`
`fncheck` option, 95
`fncreate` option, 74, 107
`_t` suffix, 134
`thisens` or `_thisens` namespace identifier
host-related binding, 58
initial context binding, 55
`thishost` or `_thishost` namespace identifier
host-related binding, 58
initial context binding, 55
`thisorgunit` or `_thisorgunit` namespace identifier
host-related binding, 58
initial context binding, 55
`thisuser` namespace identifier
initial context binding, 55
user-related binding, 56
`too many attribute values` message, 104
trailing dot (.) in organization names, 31, 38
troubleshooting
See also error messages
contexts
cannot create host- or user-related contexts, 107
cannot remove context, 107
checking naming inconsistencies, 95 to 96
debugging creation, 74
`fndestroy` does not return "operation failed", 109
`fnlist` doesn't list suborganizations, 106
`fnunbind` does not return "operation failed", 109
initial context
cannot obtain, 104
nothing in, 105
"name in use" messages, 108
"no permission" messages, 105 to 106
status codes, 151 to 153
TXT records in XFN references, 191 to 194

U

`-U`
`fnattr` option, 94
`fnbind` option, 89
`-u`, `fncheck` option, 95
`unavailable` message, 104
underscore (_)
in namespace identifiers, 41, 56
in XFN terminology, 41

UNIX hierarchical naming system, 13
updating
  bindings, 140 to 141
  FNS namespace, 95
`user` context type, 78 to 79
`user` or `_user` namespace identifier
  FNS policy, 43
  initial context binding, 55
  resolution, 41
  "shorthand" binding, 59
`username` context type, 39, 77
user-related bindings, 56 to 57
users
  as enterprise policy entities, 28
  bindings for enterprise naming, 56 to 57
  composite name examples, 29
  context creation
    all users, 74, 77
    single user, 78 to 79
    troubleshooting, 107
  context ownership, 78
  contexts, 49
  enterprise namespace, 39
  enterprise namespace policies, 43
  namespace identifier, 41
  NIS+ and FNS, 31
  view of FNS, 17 to 18

V

`-v`
  `fnbind` option, 89, 90
  `fncreate_fs(1M)` option, 121
  `fnlist` option, 85, 88, 96
  `fnlookup` option, 83, 96
verifying
  checking access control, 98 to 99
  checking context naming inconsistencies, 95 to 96
  `ctx_dir` directory creation, 71
viewing, *See* displaying; listing; lookup operations

X

`-x`, `fnbind` option, 89
X.500 global directory service
  attribute syntax for XFN references, 195 to 199
  described, 9, 63
  directory information base (DIB), 63 to 64
  federating, 63 to 65
  federating NIS+ under, 114 to ??
  FNS implementation, 9
  hierarchical naming system, 13
  name resolution, 64 to 65
X/Open Federated Naming
  attribute model, 143 to 144
  client programming interfaces, 133 to 158
    See also base attribute interface; base context interface
  abstract data types, 134
  base attribute interface, 143 to 149
  base context interface, 135 to 143
  conventions, 134
  memory management policies, 135
  overview, 133 to 135
  parameters, 153 to 155
  parsing compound names, 156 to 158
  status codes, 150 to 153
  status objects, 137, 145, 150
  supporting interfaces, 133 to 134
  usage, 134
  component separator and naming system boundaries, 161 to 163
  strong separation, 161 to 162
  weak separation, 162 to 163
  composite names, 159 to 166
  naming system boundaries and component separators, 161 to 163
  resolution, 163 to 166
  syntax, 159 to 161, 185 to 190

compound-name syntax model, 156 to 157
contexts, 12
described, 5
DNS text record format for XFN references, 191 to 194
FNS conformity, xvii, 5
FNS vs., 5
identifier formats, 154
links
composite name resolution, 165
creating and binding, 89, 90
described, 15
displaying binding, 83
error messages, 103
lookup operation, 139 to 140
status object information, 150
XFN header file, 134
XFN library, 134
object classes, 195 to 199
X.500 attribute syntax for XFN references, 195 to 199
X.500 entry supporting reference attributes, 114
XFN object class, 195 to 199
XFN, *See* X/Open Federated Naming
XFN-supplement object class, 195 to 199