Index

Symbols

.Xdefaults-host, 34

A

Adios!, 29
application class name, 19
application context, 18, 55
applications defaults file, 33
attributes, 9, 55

B

Bon jour!, 29

C

callback list, 22, 55
callback procedures, 55
callbacks, 9
    attaching to widgets, 22
    format, 24
child widget, 55
class, 56
class name, 19
client, 2
client_data, 23
client-server computing model, 2, 56
command line options, 19, 37
    creating new ones, 38
composite widget, 56
ControlArea, 20

D

device independence, 2
display, 56

F

fallback resources, 19

H

hello.c, 15
    Callback Procedure, 24
    source code, 16
    widget instance tree, 21

I

include files, 17
Inheritance, 56
instantiate, 3
instantiation, 56
internationalization, 14, 16
Intrinsics, 1

M

Makefile, 15
manager widgets, 56
mappedWhenManaged, 45

N

name, 56

O

object, 56
Ol, prefix, 19
OL_FIXEDCOLS, 28
OLIT, 57
    basic concepts, 1
    definition, 1
    example program, 39
    program structure, 13, 14
OLIT, include files, 17
OlSetDefaultTextFormat, 16
OlToolkitInitialize(), 19
OPEN LOOK, 1

P

parent widget, 57
per-user application defaults file, 33
pixel, 29
primitive widgets, 57

R

resource
    documentation, 27
resource database, 28, 32
resource file, 9
resource set of its superclass.
        instantiation, 56
resource/value pairs, 10, 19, 21
RESOURCE_MANAGER, 34
resources, 57
    applications defaults file, 33
    common, 27
    composite, 28
    core, 28
    database, 33
    default values, 22
    dynamic changing, 38
    format of value pairs, 35
    getting and setting, 30
    hardcoded, 28
    hello.c, 28
    OLIT, 27
    per-user application defaults file, 33
    pixel type, 29
    setting at creation, 21, 28
    setting color and fonts at creation, 29
    setting in resource files, 34, 36
    setting on command line, 36
    setting via database, 32
    user's defaults file, 33
    user's
        per-host defaults file, 33
    XtVaGetValues(), 31

S

server, 57
subclass, 10, 57
subwidget, 57
subwidgets, 46
superclass, 10, 58

T

top-level shell widget, 19
translator.c, 39

U

user's defaults file, 33
user's per-host defaults file, 33

W

widget, 58
    application hierarchy, 21

class hierarchy, 21
core, 28
deriving class name, 21
handle, 19
identifier, 19
instance, 3
instantiation, 20
name, 20, 46
tree, 21
widget class pointer, 20
WidgetClass, 21
widgets, 1, 3
Action, 7
children, 21
class, 3
class hierarchy, 10
composite, 28, 46, 47
Container, 7
creating, 20
main loop, 24
Manager, 7
manager, 28
names, 47
parent, 21
Popup, 7
realizing, 24
resources, 9
Text Control, 7

X

X, 1
X protocol, 2
X Server, 2, 58
X Window System, 2
X Window System Protocol, 58
X Window System Toolkit, 59
XENVIRONMENT, 15, 34
XFILESEARCHPATH, 33
Xlib, 2, 58
Xt, prefix, 19
XtAddCallback(), 22, 23
XtAppContext, 18
XtAppMainLoop, 24
XtCCallback, 23
XtNlayoutType, 28
XtNmeasures, 28
XtPointer, 19
XtRealizeWidget, 24
XtVaAppInitialize(), 19
XtVaCreateManagedWidget(), 20, 28
XtVaGetValues(), 31, 32
XtVaSetValues(), 31, 32
XtVaTypedArg, 29
XUSERFILESEARCHPATH, 33