Index

Symbols

% preprocessing directive, 36
&, server invocation and, 30

Numerics

_1 suffix, 27, 63

A

access control
    authentication vs., 99
    port monitors and, 304
`add.x` source file, 38, 39 to 41, 45 to 48, 49
adding
    address registrations, 18
    NIS+ database entries, 156
    NIS+ group members, 155
    NIS+ objects to namespace, 154
    NIS+ table entry objects, 154, 164 to 165
    port monitor services, 311
    port monitors, 302
    two numbers, 286
`ADDPROG` program, 286
addresses
    information reporting for, 20
    lookup services, 15, 18, 19
    management functions, 141
    mapping RPC services to, *See* `portmap` routine; `rpcbind` routine
    name-to-address translation routines, 17 to 18, 19, 137
    network, 295 to 296
    overview, 295 to 296
    passing arguments as, 26 to 27, 63
    passing server's address to client, 76
    passing user's bind address, 79
    registering, *See* `portmap` routine; `rpcbind` routine
    transport (netbuf), 18, 247
    universal, 17 to 18, 246, 247, 296, 333
    unregistering
        current vs. previous release, 140
        `portmap` routine, 299
        `rpcbind` routine, 18, 243, 246
        `rpcinfo` routine, 20
`ah_cred` field, 83
`ah_key` field, 100
`ah_verf` field, 83
allocating memory, *See* memory
ampersand (&), server invocation and, 30
ANSI C standards
    `rpcgen` tool and, 23, 37, 49
application programming interface (API)

NIS+, 153 to 157
applications
porting from TS-RPC to TI-RPC, 136
arguments (remote procedures)
overview, 11
passing arbitrary data types, 64 to 67
passing by address, 26 to 27, 63
passing by value, 39 to 41
passing open TLI file descriptors, 76, 79
passing server's address to client, 76
passing user's bind address, 79
`void`, 238
arrays
See also data structures
converting to XDR format, 66 to 67, 134 to 135
declarations
RPC language, 234 to 235
XDR language, 261 to 262, 270
XDR code examples, 189 to 192, 193 to 194
`assign` configuration-script keyword, 318
asynchronous mode, 88 to 90
`AUTH_BADCRED` error, 227, 228
`AUTH_BADVERF` error, 227
`AUTH_DES` authentication, 99 to 101, 220 to 226
common key, 225 to 226
conversation key, 221 to 222, 223 to 224, 226
credentials, 100, 223 to 224
described, 96, 99 to 100, 220 to 221
Diffie-Hellman encryption, 100, 222, 225 to 226
errors, 223
handle, 99 to 100
nicknames, 222 to 223, 224 to 225
protocol in XDR language, 223 to 226
server, 100 to 101
time synchronization, 100, 222 to 223
verifiers, 221 to 222, 224 to 225
`auth_destroy` routine, 96
`AUTH_KERB` authentication, 102 to 104, 226 to 230
credentials, 102, 103, 104, 227 to 229
described, 96, 102 to 104, 226
encryption, 103 to 104
errors, 227 to 228
NFS and, 226 to 228
nicknames, 103 to 104, 227, 228 to 229, 230
protocol in XDR language, 228 to 230
time synchronization, 102, 229, 230
verifiers, 103, 104, 228, 229 to 230
`AUTH_NONE` authentication, 96, 97, 218
`AUTH_REJECTEDCRED` error, 219, 227
`AUTH_REJECTEDVERF` error, 228
`AUTH_SHORT` authentication, 96
`AUTH_SHORT` verifier, 219 to 220
`AUTH_SYS` authentication, 96, 97 to 99, 218 to 220
`AUTH_TIMEEXPIRE` error, 228
`AUTH_TOOWEAK` error, 228
`AUTH_UNIX` (AUTH_SYS) authentication, 218 to 220
`AUTH_UNIX` (`AUTH_SYS`) authentication, 96, 97 to 99
`authdes_create` routine, 141
`authdes_seccreate` routine, 100, 141
authentication, 95 to 104, 218 to 230
access control vs., 99
allocating authentication numbers, 218
`AUTH_DES`, 96, 99 to 101, 220 to 226
`AUTH_KERB`, 96, 102 to 104, 226 to 230
`AUTH_NONE`, 96, 97, 218
`AUTH_SHORT`, 96, 219 to 220
`AUTH_SYS` (AUTH_UNIX), 218 to 220
`AUTH_SYS` (`AUTH_UNIX`), 96, 97 to 99
credentials
`AUTH_DES`, 100, 223 to 224
`AUTH_KERB`, 102, 103, 104, 227 to 229
described, 211 to 212
window (lifetime) of, 100, 102, 222, 223 to 224, 229

current vs. previous release, 141
destroying an, 96
errors
AUTH_DES, 223
AUTH_KERB, 227 to 228
AUTH_SYS, 99, 219
handles, 83, 99 to 100
low-level data structures and, 83
methods supported, 96
nicknames
AUTH_DES, 222 to 223, 224 to 225
AUTH_KERB, 103 to 104, 227, 228 to 229, 230
NIS+, 151
overview, 95 to 96, 218
registering authentication numbers, 218
RPC protocol and, 211 to 212
rpcgen tool and, 51, 54
servers, 96 to 97, 98 to 99, 100 to 101
service-dispatch routine and, 96 to 97
time synchronization
AUTH_DES authentication, 100, 222 to 223
AUTH_KERB authentication, 102, 229, 230
verifiers
AUTH_DES, 221 to 222
AUTH_KERB, 103, 104, 228, 229 to 230
AUTH_SYS, 219 to 220
described, 211 to 212
authkerb_seccreate routine, 102
authorization
See also authentication
NIS+, 151
authsys_create routine, 99, 141
authsys_create_default routine, 99, 141
authunix_create routine, 141
authunix_create_default routine, 141
Automatic MT mode, *See* MT Auto mode

B

batching, 92 to 95, 213, 291 to 294
bcast.c program, 90 to 91
bcast_proc routine, 91 to 92
binding
See also rpcbind routine
dynamic, 296
TI-RPC and, 11, 210
booleans
RPC language, 239
XDR language, 255
bottom level interface routines (RPC), 15, 80 to 82
broadcast RPC, 90 to 92
current vs. previous release, 140 to 141
overview, 90, 214
portmap routine and, 297, 300
routines for, 13, 90 to 92
rpcbind routine and, 240, 248
server response to, 50, 52, 91, 92
TS-RPC vs. TI-RPC, 143 to 145
buffer size
specifying send and receive, 76, 79
byte arrays
See also arrays
XDR, 189

C

C
rpcgen tool and
ANSI C compliance, 23, 37, 49
C-style mode, 22, 37, 39 to 41, 238
preprocessing directives, 35 to 37, 50, 51
SPARCompiler C++ 3.0 compatibility, 49
XDR routines and, 175
caching
NIS+, 153
server, 82
call semantics
TI-RPC, 12, 209

callback procedures
NIS+, 166, 168
transient RPC program numbers and, 109 to 110
uses for, 109 to 110
`callrpc` routine, 140
CBC (cipher block chaining) mode, 103
`cd` command, 319
changing
NIS+ objects in namespace, 154
NIS+ table entry objects, 154
port monitor configuration scripts, 319 to 321
port monitor services, 311
version numbers of programs, 106
cipher block chaining (CBC) mode, 103
`circuit_n` transport type, 16
`circuit_v` transport type, 16
circuit-oriented transports
when to use, 17
`cl_auth` field, 83, 96
`cl_netid` field, 80 to 81
`cl_private` field, 81
`cl_tp` field, 80 to 81
classes of messages, 309
client authentication, *See* authentication
client handles
creating
bottom level interface, 15, 81
current vs. previous release, 139
expert level interface, 15, 76 to 78
intermediate level interface, 14, 73 to 74
top level interface, 14, 28 to 29, 68 to 70
defined, 331
destroying
current vs. previous release, 139
expert level interface, 78
top level interface, 28, 70
low-level data structures for, 82 to 83
client programs
remote copy, 132 to 133
`rpcgen` tool and
ANSI C-compliance, 49
complex data structure passing, 33 to 35
debugging, 56 to 57
directory listing service, 33 to 35, 284 to 285
message printing code example, 27 to 30
MT-safety, 22, 45 to 47
overview, 23, 27 to 30
simplified interface, 61 to 62
client stub routines
`rpcgen` tool and, 21, 28, 29
C-style mode, 40 to 41
MT Auto mode, 48
MT-safe, 42 to 43
MT-unsafe, 43 to 44
preprocessing directive, 36
client templates
`rpcgen` tool, 22, 37, 38, 39 to 41
client time-out periods
creating timed clients, 14, 70, 74
`rpcgen` tool and, 51, 53
clients
batched, 92 to 94, 291 to 292
defined, 331, 332
multiple versions, 108 to 109
multithreaded
overview, 111 to 116
safety, 42 to 44, 45 to 47, 59, 332
User mode, 123, 124 to 126
NIS+, 153
transaction IDs and, 209
TS-RPC vs. TI-RPC, 142 to 143
`_clnt.c` suffix, 29
`clnt_broadcast` routine, 140, 143 to 144
`clnt_call` routine
current vs. previous release, 140
described, 14, 15
`RPCPROGVERSMISMATCH` error, 108
simplified interface and, 68
top level interface and, 70
`clnt_control` routine

current vs. previous release, 139
described, 53, 78
simplified interface and, 68
using, 53
clnt_create routine
code example, 27 to 29
current vs. previous release, 139
described, 14
clnt_create_timed routine
current vs. previous release, 139
described, 14
using, 70
clnt_create_vers routine, 108, 139
clnt_destroy routine
current vs. previous release, 139
described, 28, 70, 78
simplified interface and, 68
clnt_dg_create routine
current vs. previous release, 139
described, 15, 81
using, 81
clnt_ops field, 81
clnt_pcreateerror routine
current vs. previous release, 139
described, 70
simplified interface and, 68
clnt_perrno routine, 68
clnt_perror routine, 57, 68
clnt_raw_create routine, 85 to 87, 139
clnt_spcreateerror routine, 139
clnt_sperror routine, 57
clnt_tli_create routine
current vs. previous release, 139
described, 15, 76, 80 to 81
using, 76, 78
clnt_tp_create routine, 14, 139
clnt_tp_create_timed routine
current vs. previous release, 139
described, 14
using, 74
clnt_vc_create routine
current vs. previous release, 139
described, 15, 81
using, 81
clntraw_create routine, 139
clnttcp_create routine, 139
clntudp_bufcreate routine, 139
clntudp_create routine, 76 to 78, 139
clock synchronization, *See* time synchronization
comments
XDR language, 267
compatibility
library functions, current vs. previous release, 139 to 142
compilation
NIS+, 158
rpcgen tool, 22, 39 to 41
complex data structures
See also data structures
packing with xdr_inline, 37, 50
rpcgen tool and, 30 to 35
compound data type filters
XDR, 66 to 67, 187
_config file, 315, 316, 317, 320, 330
configuration scripts, *See* port monitors, configuration scripts
connectionless transports
See also datagram transports; UDP (user datagram protocol)
client handle creation for, 15
defined, 331
nettype parameters for, 16
server handle creation for, 15
connection-oriented endpoints, 85
connection-oriented transports
See also TCP (transport control protocol)
client handle creation for, 15
defined, 331
nettype parameters for, 16
port monitors and, 104 to 105
remote copy code example, 131 to 134
server handle creation for, 15
constants
RPC language, 233

XDR language, 265, 267, 270
constructed data type filters
XDR, 66 to 67, 187
conversation key
AUTH_DES authentication, 221 to 222, 223 to 224, 226
converting
addresses, 17 to 18, 19, 137
from XDR format, 64, 67, 72, 134, 135, 181 to 182, 331
local procedures to remote procedures, 23 to 30
to XDR format, 30 to 35, 64 to 67, 134 to 135, 177 to 179, 181 to 182, 332
copying
NIS+ database entries, 156
NIS+ objects, 157
NIS+ table entry objects, 154
remote, 131 to 134
counted byte strings, *See* string declarations; string representation
cpp directive
rpcgen tool and, 37
crashes
server, 209, 223
creating
client handles, *See* client handles, creating
NIS+ databases, 155
NIS+ directory objects, 162
NIS+ group objects, 155, 163
NIS+ table objects, 163 to 165
server handles, *See* server handles, creating
utmp entries, 305, 312, 316
credentials
AUTH_DES, 100, 223 to 224
AUTH_KERB, 102, 103, 104, 227 to 229
described, 211 to 212
window (lifetime) of, 100, 102, 222, 223 to 224, 229
C-style mode
rpcgen tool, 22, 37, 39 to 41, 238

D

daemons
kerbd, 226, 227
rpcbind, 19, 90
data representation
See also XDR (external data representation)
TI-RPC, 12
data structures
See also arrays; structure declarations
converting to XDR format, 30 to 35, 64 to 67, 134 to 135, 179, 181 to 182
low-level, 82 to 85
MT safe, 123
packing with xdr_inline, 37, 50
recursive, 203 to 206, 266
rpcgen tool and, 30 to 35
data types
passing arbitrary, 64 to 67
database access functions (NIS+), 153, 155, 156
datagram transports
See also UDP (user datagram protocol)
broadcast RPC and, 90
defined, 331
nettype parameters, 16
when to use, 17
datagram_n transport type, 16
datagram_v transport type, 16
date service
intermediate level client for, 73 to 74
intermediate level server for, 74 to 75
top level client for trivial, 69 to 70
top level server for, 71 to 72
db_add_entry function, 156
db_checkpoint function, 156
db_first_entry function, 156
db_list_entries function, 156
db_next_entry function, 156
db_remove_entry function, 156

`db_reset_next_entry` function, 156
`db_standby` function, 156
`dbxtool` routine, 56
deallocating memory, *See* memory, releasing
debugging
  raw mode and, 85 to 87
  `rpcgen` tool and, 50, 51, 56 to 57
declarations
  RPC language, 234 to 240
  XDR language, 253 to 266
defaults
  maximum number of threads, 119
  `rpcgen` tool, *See* `rpcgen` tool, defaults
  single-threaded mode, 117
define statements, command line, `rpcgen` tool, 50, 51
definitions
  RPC language, 231 to 232, 272
deleting
  See also destroying; memory, releasing
  address registrations, 140
  address registrations, *See* unregistering
  assocations, 15
  mappings, 15
  NIS+ database entries, 156
  NIS+ directory from host, 155
  NIS+ group members, 155
  NIS+ group objects, 155, 169 to 173
  NIS+ objects from namespace, 154, 168 to 169
  NIS+ table entry objects, 154, 169 to 173
  port monitor services, 311
  port monitors, 302
DES encryption, 100, 103 to 104, 222, 225 to 226
deserializing, 64, 67, 72, 134, 135, 181 to 182, 331
  See also XDR (external data representation)
destroying
  See also deleting
  client authentication handles, 96
  client handles, 28, 70, 78, 139
  NIS+ objects, 157
  server handles, 139
  XDR streams, 198
Diffie-Hellman encryption, 100, 222, 225 to 226
`dir.x` program, 30 to 32, 281 to 282
`dir_proc.c` routine, 32 to 33, 282 to 283
`dir_remove` function, 170
directories
  remote directory listing service, 30 to 35, 281 to 285
  SAF (service access facility), 329 to 330
disabling port monitors, 304, 307
discriminated unions
  declarations
    RPC language, 236 to 237
    XDR language, 236 to 237, 263 to 264, 270
  XDR code samples, 194 to 196
dispatch tables
  `rpcgen` tool, 50, 55 to 56
`doconfig` function, 305, 314, 316 to 317
domains (NIS+)
  administration commands, 153
  functions, 155, 157
  overview, 149 to 150
dynamic binding, 296
dynamic program numbers, 109 to 110, 212

E

ECB (electronic code book) mode, 103, 104
electronic code book (ECB) mode, 103
enabling
  port monitors, 304, 307
  server caching, 82
encryption

AUTH_DES authentication (Diffie-Hellman), 100, 222, 225 to 226
AUTH_KERB authentication, 103 to 104
endnetconfig routine, 78
endpoints
connection-oriented, 85
enumeration filters
XDR primitives, 186 to 187
enumerations
RPC language, 31, 232 to 233
XDR language, 254 to 255
errors
authentication
AUTH_DES, 223
AUTH_KERB, 227 to 228
AUTH_SYS, 99, 219
client handle creation, 70
multiple client version, 108
NIS+ error message display functions, 153, 156
RPC, 29, 56 to 57, 211
thr_create, 119
/etc/inet/inetd.conf file, 105
/etc/netconfig database, 16, 51, 138
/etc/rpc database, 12
/etc/saf/_pid file, 305, 315, 322, 330
/etc/saf/*pmtag* directory, 329
/etc/saf/*pmtag*/_config file, 315, 316, 317, 320, 330
, 315
/etc/saf/*pmtag*/_pmpipe file, 307, 315, 330
/etc/saf/*pmtag*/_pmtab file, 306, 311 to 312, 315, 330
/etc/saf/*pmtag*/svctag file, 311 to 312, 315, 316, 330
/etc/saf/_sactab files, 310, 329
/etc/saf/_sysconfig file, 316, 317, 319 to 320, 329
expert level interface routines (RPC), 15, 75 to 80
client, 76 to 78
overview, 15, 75
server, 79 to 80
external data representation, *See* XDR (external data representation)

F

file data structure
XDR language, 270 to 271
file descriptors, passing open TLI, 76, 79
file system, *See* NFS (network file system)
filters (XDR)
arrays, 189 to 192, 193 to 194
constructed (compound) data type, 66 to 67, 187
enumeration, 186 to 187
floating point, 65, 186
number, 65 to 66, 185 to 186
opaque data, 192 to 193
strings, 67, 187 to 188
unions, 194 to 196
fixed-length arrays
See also arrays
declarations
RPC language, 234 to 235
XDR language, 261 to 262
XDR code sample, 193 to 194
fixed-length opaque data
XDR language, 258 to 259
flags, *See* rpcgen tool, flags
floating point
XDR language, 256 to 258
floating point filters
XDR primitives, 65, 186
free routine, 35
freeing resources
See deleting; destroying; disabling port monitors; memory, releasing
freenetconfigent routine, 74

G

`getnetconfig` routine, 78
`getnetconfigent` routine, 73, 74
glossary, 331 to 333
groups (NIS+)
  administration commands, 152
  manipulation functions, 153, 155
  sample programs, 163, 169 to 173

H

hand-coded registration routine, 64
handles
  See also client handles; server handles; transport handles
  authentication, 83, 99 to 100
  defined, 331
header files
  `rpcgen` tool and, 29, 36
host/service pairs
  translation to/from `netbuf` addresses, 18
hosts
  defined, 332
hyper integers
  XDR language, 255 to 256

I

`.i` suffix, 55
I/O streams
  XDR, 199
idempotent
  defined, 12
identifiers
  XDR language, 267
identifying
  See also authentication; naming
  port monitor services, 311
  remote procedures, 12, 209, 210 to 213
index table
  `rpcgen` tool and, 36
indirect RPC, 244, 245, 248
`inetd` port monitor
  RPC services, 105
  `rpcgen` tool and, 30, 52 to 53
  using, 104, 105
`inetd.conf` file, 105
information reporting
  addresses, 20
  NIS+, 155, 156
  remote host status, 111 to 116
  RPC, 20
  `rpcbind` server, 248
  server callbacks, 109 to 110
installing port monitor configuration scripts, 319 to 321
integers
  XDR language, 177 to 178
integers, XDR language, 253 to 254, 255 to 256
interfaces, *See* RPC (remote procedure call), interface routines; SAF (service access facility)
intermediate level interface routines (RPC), 14, 73 to 75
Internet protocols, *See* TCP (transport control protocol); UDP (user datagram protocol)
`ISTATE` environment variable, 304, 306 to 307, 315

K

`kerbd` daemon, 226, 227
Kerberos authentication, *See* `AUTH_KERB` authentication
keywords
  RPC language, 31
  XDR language, 269
`KGETKCRED` procedure, 226, 227
`KGETUCRED` procedure, 226, 227 to 228
`KSETKCRED` procedure, 226, 227

L

`lib` library, 35

`libc` library, 137, 138
`libnsl` library, 29, 32, 137, 138
libraries
  `lib`, 35
  `libc`, 137, 138
  `libnsl`, 29, 32, 137, 138
  `librpcsvc`, 60
  `lthread`, 112
  RPC functions, 139 to 142
  `rpcgen` tool and
    `libnsl`, 29, 32, 137, 138
    selecting TI-RPC or TS-RPC library, 23, 37, 49
  XDR, 180 to 182
    See also XDR (external data representation) primitive routines
`librpcsvc` library, 60
lifetime of credentials, *See* window of credentials
limits
  broadcast request size, 90
  maximum number of threads, 119
linked lists
  XDR, 203 to 206, 266
`listen` port monitor
  administrative command for, 306
  `rpcgen` tool and, 30, 52 to 53
  using, 104, 105 to 106
listing
  See also printing
  NIS+ objects, 157, 166 to 168
  NIS+ principals, 155
  NIS+ servers, 156
  NIS+ table objects, 154, 166 to 168
  `portmap` mappings, 300
  remote directory listing service, 30 to 35, 281 to 285
  `rpcbind` addresses, 248
  `rpcbind` mappings, 12, 243, 246
live code examples, 281 to 294
  adding two numbers program, 286
  batched code, 291 to 294
  directory listing program, 281 to 285
  print message program, 287 to 291
  spray packets program, 286 to 287
  time server program, 285
loading, *See* binding
local procedures
  converting to remote procedures, 23 to 30
locks
  mutex, multithreaded mode and, 117
  port monitor IDs and lock files, 305, 315, 330
`_log` file
  SAC (service access controller), 330
log functions
  NIS+ transaction, 153, 156
low-level data structures, 82 to 85
`lthread` library, 112

M

`main` server function, 52
makefile templates
  `rpcgen` tool, 22, 38
mapping, 15
  See also `portmap` routine; `rpcbind` routine
master servers
  NIS+, 150, 153, 172
maximums
  broadcast request size, 90
  number of threads, 119
memory
  allocating with XDR, 134 to 135
  releasing
    , 45
    `clnt_destroy` routine, 28, 68, 70, 78
    `free` routine, 35
    NIS+, 154, 155, 156
    simplified interface and, 68
    `svc_done` routine, 123
    `svc_freeargs` routine, 135
    `XDR_FREE` operation, 187
    `xdr_free` routine, 35, 45

XDR primitive requirements for, 183 to 185, 187
memory streams
XDR, 199
mesg_proc.c routine, 290 to 291
message classes, 309
message interface (SAF), 306 to 309, 315, 321 to 327, 330
messageprog_1_freeresult routine, 45
modifying, *See* changing
msg.h header file, 29
msg.x program, 42, 290
msg_clnt.c routine, 29
msg_svc.c program, 29
msg_svc.c routine, 29
MT Auto mode, 117, 119 to 122
code examples, 120 to 122
described, 117, 119
rpcgen tool and, 22, 37, 48
service transport handle and, 118
MT hot
defined, 332
MT RPC programming, *See* multithreaded RPC programming
MT User mode, 117, 118, 123 to 130
MT-safe code
clients, 22, 42 to 44, 45 to 47, 59, 332
defined, 332
rpcgen tool and, 22, 37, 42 to 48
servers, 22, 44 to 45, 47 to 48, 59, 117, 332
multiple client versions, 108 to 109
multiple server versions, 106 to 108
multithreaded Auto mode, *See* MT Auto mode
multithreaded hot
defined, 332
multithreaded RPC programming, 111 to 130
clients
overview, 111 to 116
safety, 22, 42 to 44, 45 to 47, 59, 332
User mode, 123, 124 to 126
library, 112
maximum number of threads, 119
overview, 111
performance enhancement, 120, 127
rpcgen tool and, 22, 37, 42 to 48
servers
Auto mode, 22, 37, 48, 117, 118, 119 to 122
overview, 111, 116 to 118
safety, 22, 44 to 45, 47 to 48, 59, 117, 332
timing diagram, 118
unsafe routines, 117
User mode, 117, 118, 123, 127 to 130
multithreaded User mode, 117, 118, 123 to 130
multithreaded-safe code, *See* MT-safe code
mutex locks
multithreaded mode and, 117

N

Name Service Switch, 152
name-to-address translation, 17 to 18, 19, 137
naming
See also identifying; NIS+ (Network Information Services Plus)
client stub programs by rpcgen, 29
netnames, 100, 221
programs by version number, 106
remote procedure calls by rpcgen, 27
server programs by rpcgen, 29
standard for, 221
template files for rpcgen, 38
naming service, *See* NIS+ (Network Information Services Plus)
netbuf addresses, 18, 247
netconfig database, 16, 51, 138

netdir_getbyaddr routine, 18
netdir_getbyname routine, 18
netnames, 100, 221
NETPATH environment variable, 16, 51, 70
nettype parameters, 16
network addresses, *See* addresses
network file system, *See* NFS (network file system)
Network Information Services Plus, *See* NIS+ (Network Information Services Plus)
network names, 100, 221
network pipes, 177
network selection
  RPC, 16
  rpcgen tool, 50, 51
network services
  defined, 332
Newstyle (C-style) mode
  rpcgen tool, 22, 37, 39 to 41
NFS (network file system)
  described, 4
  Kerberos authentication and, 226 to 228
NFSPROC_GETATTR procedure, 227
NFSPROC_STATVFS procedure, 228
nicknames
  AUTH_DES, 222 to 223, 224 to 225
  AUTH_KERB, 103 to 104, 227, 228 to 229, 230
NIS+
  servers
    sample program, 172
NIS+ (Network Information Services Plus), 149 to 173
  application programming interface (API), 153 to 157
  cache administration commands, 153
  client administration commands, 153
  compilation, 158
  database access functions, 153, 155, 156
  domains
    administration commands, 153
    functions, 155, 157
    overview, 149 to 150
  error message display functions, 153, 156
  groups
    administration commands, 152
    manipulation functions, 153, 155
    sample programs, 163, 169 to 173
  local name functions, 153, 155, 157
  miscellaneous functions, 153, 157
  Name Service Switch, 152
  namespace administration commands, 152 to 153
  objects
    administration commands, 152, 153
    manipulation functions, 153, 154, 157
    sample programs, 158 to 173
  overview, 5, 149 to 153
  sample program, 157 to 173
  security, 151
    administration commands, 152
  servers
    administration commands, 153
    functions, 153, 155 to 156
    overview, 150
  tables
    access functions, 153, 154
    administration commands, 152
    overview, 150 to 151
    sample programs, 163 to 165
  time synchronization, 156
  transaction log functions, 153, 156
  unsupported macros, 158
nis_add function, 154, 158, 162, 164
nis_add_entry function, 154, 158, 165
nis_addmember function, 155, 158, 161
nis_admin functions, 156
nis_cachemgr command, 153
nis_checkpoint function, 157
nis_clone_object function, 157

nis_creategroup function, 155, 158, 163
nis_db functions, 156
nis_destroy_object function, 157
nis_destroygroup function, 155, 158, 169 to 170
nis_dir_cmp function, 157
nis_domain_of function, 157, 158
nis_error functions, 156
nis_first_entry function, 154
nis_freenames function, 155
nis_freeresult function, 154, 158
nis_freeservlist function, 156
nis_freetags function, 156
nis_getnames function, 155
nis_getservlist function, 156
nis_groups functions, 155
nis_ismember function, 155
nis_leaf_of function, 157, 158, 167
nis_lerror function, 156
nis_list function, 154, 158, 166 to 168
nis_local_directory function, 155, 158, 159
nis_local_group function, 155
nis_local_host function, 155
nis_local_names functions, 155
nis_local_principal function, 155, 158, 159
nis_lookup function, 154, 158 to 160, 165, 166 to 167
nis_mkdir function, 155, 158, 162
nis_modify function, 154
nis_modify_entry function, 154
nis_name_of function, 157
nis_names functions, 154
nis_next_entry function, 155
nis_perror function, 156, 158
nis_ping function, 156
nis_print_group_entry function, 155
nis_print_object function, 157
nis_remove function, 154, 158, 162, 168 to 169, 170
nis_remove_entry function, 154, 158, 169, 170
nis_removemember function, 155, 158, 170
nis_rmdir function, 155
nis_server functions, 155 to 156
nis_servstate function, 156
nis_sperrno function, 156
nis_sperror function, 156
nis_stats function, 156
nis_subr functions, 157
nis_tables functions, 154
nis_verifygroup function, 155
nisaddcred command, 152
nisaddent command, 152
niscat command, 152
nischgrp command, 152
nischmod command, 152
nischown command, 152
nischttl command, 153
nisdefaults command, 153
nisgrep command, 152
nisgrpadm command, 152
nisinit command, 153
nisln command, 153
nisls command, 152
nismatch command, 152
nismkdir command, 153
nispasswd command, 152
nisrm command, 153
nisrmdir command, 153
nissetup command, 153
nisshowcache command, 153
nistbladm command, 152
nisupdkeys command, 152
nlsadmin command, 306
no-data routine
XDR, 187
NULL arguments, 63

NULL pointers, 197
NULL strings, 239
NULL transport type, 16
number filters, XDR, 65 to 66, 185 to 186
    See also xdr_long routine
number of users
    on a network, 98 to 99
    on a remote host, 60
numbers
    See also floating point; integers; port numbers; procedure numbers; program numbers; version numbers
    adding two, 286

O

objects (NIS+)
    administration commands, 152, 153
    manipulation functions, 153, 154, 157
    sample programs, 158, 158 to 173
ONC+ overview, 3 to 5
opaque data
    declarations
        RPC language, 239
        XDR language, 258 to 260
    XDR code examples, 192 to 193
open TLI file descriptors
    passing, 76, 79
optional-data unions
    XDR language, 266

P

parameters, *See* arguments
passing parameters, *See* arguments
percent sign (%), preprocessing directive, 36
_pid file, 305, 315, 322, 330
ping program, 230 to 231, 332
pipes
    network, 177
    _pmpipe file, 307, 315, 330
    _sacpipe file, 307, 315, 330
pm_maxclass field, 309
pm_size field, 308, 309
pmadm command, 105 to 106, 306, 311, 313, 320 to 321
pmap_getmaps routine, 141
pmap_getport routine, 141 to 142
pmap_rmtcall routine, 141
pmap_set routine, 141
pmap_unset routine, 141
PMAPPROC_CALLIT procedure, 300
PMAPPROC_DUMP procedure, 300
PMAPPROC_GETPORT procedure, 299
PMAPPROC_NULL procedure, 299
PMAPPROC_SET procedure, 299
PMAPPROC_UNSET procedure, 299
pmmsg structure, 308
_pmpipe file, 307, 315, 330
_pmtab file, 306, 311 to 312, 315, 330
/*pmtag* directory, 306, 311, 330
/pmtag directory, 329
PMTAG environment variable, 306, 315
pointers
    remote procedures, 26 to 27
    RPC language, 235 to 236
    XDR code examples, 196 to 197
poll routine, 88 to 90
pop configuration-script keyword, 318
port monitors
    activity monitoring, 304
    adding, 302
    adding services, 311
    administrative commands
        monitor-specific command, 313 to 314
        pmadm, 105 to 106, 306, 311, 313, 320 to 321
        sacadm, 106, 302, 310, 312 to 313, 319 to 320
    administrative files
        _pmtab, 306, 311 to 312, 315, 330
        _sactab, 329, 310
    administrative interface, 309 to 316

changing port monitor services, 311
configuration scripts, 316 to 321
installing, 319 to 321
language for writing, 318 to 319
per-port monitor, 315, 316, 317, 320, 330
per-service, 305, 306, 314, 315, 316, 317 to 318, 320 to 321, 330
per-system, 316, 317, 319 to 320, 329
printing, 319 to 321
replacing, 319 to 321
deleting services, 311
disabling, 304, 307
enabling, 304, 307
files
administrative, 306, 310, 311 to 312, 315, 329, 330
key, 315
per-port monitor configuration, 315, 316, 317, 320, 330
per-service configuration, 305, 306, 314, 315, 316, 320 to 321, 330
per-system configuration, 316, 317, 319 to 320, 329
private, 306, 311
process ID, 305, 315, 330
functions, 303 to 305, 315 to 316
home directory for, 329
identifying services, 311
management function, 303
message interface, 306 to 309, 315, 321 to 327, 330
`_pmpipe` file, 307, 315, 330
private files, 306, 311
process IDs and lock files, 305, 315, 330
removing, 302
requirements for implementing, 314 to 315
restricting access to system, 304
`rpcgen` tool and, 30, 50, 52 to 53
sample code, 321 to 327
service interface, 314
terminating, 305, 315
types of, 310
using, 104 to 106
`utmp` entry creation, 305, 312, 316
version numbers, 312, 313 to 314
writing with service access facility, *See* SAF (service access facility)
port numbers
getting for registered services, 141 to 142, 295 to 300
`portmap` routine, 299
`rpcbind` routine, 19, 245
TCP/IP protocol, 19, 245, 299
UDP/IP protocol, 19, 245, 299
porting data, *See* XDR (external data representation)
porting TS-RPC to TI-RPC, 136 to 145
applications, 136
benefits, 136
code comparison examples, 142 to 145
differences between TI-RPC and TS-RPC, 138, 142 to 145
function compatibility lists, 139 to 142
`libc` library and, 137
`libnsl` library and, 137
name-to-address mapping and, 137
old interfaces and, 137
`portmap` routine, 295 to 300
address management functions, 141
broadcast RPC and, 297, 300
operation of, 299 to 300
overview, 295 to 296
port number, 299
protocol specification for, 296 to 298
replacement of, 18, 295
TS-RPC and, 138
ports
defined, 303
preprocessing directives
`rpcgen` tool, 35 to 37, 50, 51
printing
See also listing

message to system console, 23 to 30, 287 to 291
port monitor configuration scripts, 319 to 321
`printmsg.c` program
remote version, 24 to 30, 288 to 291
single process version, 23 to 24, 287 to 288
procedure numbers
described, 12, 210
error conditions, 211
procedure-lists
RPC language, 232
procedures
registering as RPC programs, 13, 64
RPC language, 232
program declarations
RPC language, 237 to 238
program numbers, 210 to 213
See also version numbers
assigning, 212 to 213
described, 12, 210
error conditions, 211
mapping, *See* `portmap` routine; `rpcbind` routine
registering, 213
transient (dynamically assigned), 109 to 110, 212
program-definitions
RPC language, 232
`PROGVERS` program name, 106
`PROGVERS_ORIG` program name, 106
protocols
See also TI-RPC (transport-independent remote procedure call), protocol; transport protocols; XDR language
`AUTH_DES`, 223 to 226
`rpcbind` protocol specification, 240 to 245
specifying in RPC language, 24
`push` configuration-script keyword, 318

Q

quadruple-precision floating point
XDR language, 257 to 258

R

raw RPC
testing programs using low-level, 85 to 87
`READDIR` procedure, 30 to 35, 281 to 285
record streams
XDR, 199 to 201, 217 to 218
record-marking standard, 217 to 218
recursive data structures, 203 to 206, 266
registering
addresses, *See* `portmap` routine; `rpcbind` routine
authentication numbers, 218
current vs. previous release, 140
hand-coded registration routine, 64
procedures as RPC programs, 13, 63, 64
program numbers, 213
program version numbers, 106
`registerrpc` routine, 140
releasing memory, *See* memory, releasing
remote copy routine, 131 to 134
remote directory listing service, 30 to 35
remote procedure call, *See* RPC (remote procedure call)
remote procedures
converting local procedures to, 23 to 30
identifying, 12, 209, 210 to 213
remote time protocol, 36, 48
removing, *See* deleting; destroying; freeing resources
rendezvousing
TI-RPC and, 210
`rpcgen` tool
flags
-Sc (templates), 38
replacing, *See* changing

replica servers
NIS+, 150, 153
reporting, *See* information reporting
`rls.c` routine, 33 to 35, 284 to 285
RPC (remote procedure call)
See also authentication; multithreaded RPC programming; RPC language (RPCL); `rpcgen` tool
address lookup services, 15, 18, 19
address registration, *See* `portmap` routine; `rpcbind` routine
address reporting, 20
address translation, 17 to 18, 19, 137
asynchronous mode, 88 to 90
batching, 92 to 95, 213, 291 to 294
broadcast, *See* broadcast RPC
described, 9 to 10, 208
errors, 29, 56 to 57, 211
failure of, 29
identifying remote procedures, 12, 209, 210 to 213
indirect, 244, 245, 248
information reporting, 20, 109 to 110
interface routines, 13 to 15, 59 to 82
bottom level, 15, 80 to 82
caching servers, 82
expert level, 15, 75 to 80
intermediate level, 14, 73 to 75
low-level data structures, 82 to 85
overview, 13 to 15, 59 to 60, 68
simplified, 13, 60 to 67, 68
standard, 13 to 15, 68 to 85
top level, 14, 28 to 29, 68 to 72
interface routines, *See* TI-RPC (transport-independent remote procedure call), interface routines
multiple client versions, 108 to 109
multiple server versions, 106 to 108
name-to-address translation, 17 to 18, 19, 137
network selection, 16
`poll` routine, 88 to 90
port monitor usage, 104 to 106
protocol, *See* TI-RPC (transport-independent remote procedure call) protocol
raw, testing programs using low-level, 85
record-marking standard, 217 to 218
standards, 10, 217 to 218
transient RPC program numbers, 109 to 110, 212
transport selection, 17 to 18
transport types, 16
RPC language
reference, 272 to 279
RPC language (RPCL), 230 to 240
See also `rpcgen` tool
arrays, 234 to 235
booleans, 239
C vs., 21
constants, 233
C-style mode and, 238
declarations, 234 to 235
definitions, 231 to 232, 272
discriminated unions, 31, 236 to 237
enumerations, 31, 232 to 233
example protocol described in, 24
example service described in, 230 to 231
fixed-length arrays, 234 to 235
keywords, 31
opaque data, 239
overview, 272, 332
pointers, 235 to 236
`portmap` protocol specification in, 297 to 298
program declarations, 237 to 238
simple declarations, 234
special cases, 238 to 240
specification for, 230 to 240
strings, 25, 239
structures, 31, 236
syntax, 231 to 232, 272
type definitions, 233
unions, 31, 236 to 237

variable-length arrays, 235
voids, 240
XDR language vs., 230, 232, 272
rpc.nisd command, 153
RPC/XDR, *See* RPC language (RPCL)
RPC_AUTHERROR error, 223
rpc_broadcast routine
current vs. previous release, 141, 143
described, 13
source code, 144 to 145
using, 90 to 92
rpc_call routine
current vs. previous release, 140
described, 13, 61
using, 61, 62
RPC_CLNT preprocessing directive, 36
rpc_control routine, 117, 119, 123
rpc_createerr global variable, 70
__rpc_dtbsize function, 88, 89
RPC_HDR preprocessing directive, 36
rpc_reg routine
current vs. previous release, 140
described, 13
using, 63, 64
__rpc_select_to_poll function, 88, 89
RPC_SVC preprocessing directive, 36
RPC_SVC_MTMODE_GET library routine, 119, 123
RPC_SVC_MTMODE_SET library routine, 119
RPC_SVC_THRCREATES_GET library routine, 119
RPC_SVC_THRERRORS_GET library routine, 119
RPC_SVC_THRMAX_GET library routine, 119
RPC_SVC_THRMAX_SET library routine, 119
RPC_SVC_THRTOTAL_GET library routine, 119
RPC_TBL preprocessing directive, 36
RPC_XDR preprocessing directive, 36
rpcb_getaddr routine, 15, 141 to 142
rpcb_getmaps routine, 141
rpcb_gettime routine, 141
rpcb_rmtcall routine, 141
rpcb_set routine
current vs. previous release, 141
described, 15, 79
rpcb_unset routine, 15, 141
rpcbind daemons
broadcast RPC and, 90
registering addresses with, 19
rpcbind routine
See also specific procedures
address management functions, 141
broadcast RPC and, 240, 248
calling, 15
described, 11, 18 to 19, 138, 141, 222, 240
listing mappings, 12, 243, 246
operation of, 245 to 248
port number, 19, 245
portmap routine replaced by, 18, 295
protocol specification for, 240 to 245
time service, 141, 222, 247
version 4, 247 to 248
RPCBPROC_BCAST procedure, 244, 248
RPCBPROC_CALLIT procedure, 19, 243, 247, 248
RPCBPROC_DUMP procedure, 243, 246
RPCBPROC_GETADDR procedure, 243, 246
RPCBPROC_GETADDRLIST procedure, 245, 248
RPCBPROC_GETSTAT procedure, 245, 248
RPCBPROC_GETTIME procedure, 222, 244, 247
RPCBPROC_GETVERSADDR procedure, 244 to 245, 248
RPCBPROC_INDIRECT procedure, 244, 245, 248
RPCBPROC_NULL procedure, 243, 245
RPCBPROC_SET procedure, 243, 246, 248
RPCBPROC_TADDR2UADDR procedure, 244, 247

RPCBPROC_UADDR2TADDR
procedure, 244, 247
RPCBPROC_UNSET procedure, 243, 246, 248
rpcgen tool, 21 to 57
add two numbers program, 286
advantages, 22
arguments, 26 to 27, 39 to 41, 63, 64 to 67, 238
authentication and, 51, 54, 99 to 104
batched code example, 291 to 294
broadcast call server response, 50, 52
C and
ANSI C compliance, 23, 37, 49
C-style mode, 22, 37, 39 to 41, 238
preprocessing directives, 35 to 37, 50, 51
SPARCompiler C++ 3.0 compatibility, 49
client handles and, *See* client handles
client programs and, *See* client programs
client stub routines and, *See* client stub routines
compilation modes, 22, 39 to 41
complex data structure passing, 30 to 35
converting local procedures to remote procedures, 23 to 30
cpp directive, 37
debugging, 50, 51, 56 to 57
defaults
argument passing mode, 39, 40 to 41
C preprocessor, 37
client time-out period, 53
compilation mode, 22
library selection, 49
MT-safety, 22, 42
output, 21
server exit interval, 53
define statements on command line, 50, 51
described, 21 to 22
directory listing program, 30 to 35, 281 to 285
dispatch tables, 50, 55 to 56
failure of remote procedure calls, 29
flags
-A (MT Auto mode), 37, 48
-a (templates), 37, 38
-b (TS-RPC library), 37, 49
-i (xdr_inline count), 37, 50
listed, 37
-M (MT-safe code), 37, 42
-N (C-style mode), 37, 39
-Sc (templates), 37
-Sm (templates), 37, 38
-Ss (templates), 37, 38
hand-coding vs., 64
handles and, *See* client handles; server handles
libraries
libnsl, 29, 32, 137, 138
selecting TI-RPC or TS-RPC library, 23, 37, 49
MT (multithread) Auto mode, 22, 37, 48, 119 to 122
MT (multithread)-safe code, 22, 37, 42 to 48
naming remote procedure calls, 27
network types/transport selection, 50, 51
Newstyle (C-style) mode, 22, 37, 39 to 41
optional output, 21
pointers, 26 to 27
port monitor support, 30, 50, 52 to 53
preprocessing directives, 35 to 37, 50, 51
print message program, 23 to 30, 287 to 291
programming techniques, 50 to 57
server handles and, *See* server handles
server programs and, *See* server programs
server stub routines and, *See* server stub routines
socket functions and, 49
spray packets program, 286 to 287

stub routines and, *See* client stub routines; server stub routines
SunOS 5.x features, 22 to 23
templates, 22, 37, 38, 39 to 41
time server program, 36, 48, 285
time-out changes, 51, 53
TI-RPC vs. TS-RPC, 138
TI-RPC vs. TS-RPC library selection, 23, 37, 49
tutorial, 23 to 37
variable declarations and, 234
XDR routine generation, 30 to 35, 36, 175
`xdr_inline` count, 37, 50
`rpcinfo` routine, 19, 20
`RPCPROGVERSMISMATCH` error, 108
`/rpcsvc` directory, 213
`rprintmsg` routine, 30
`rq_clntcred` field, 97
`rq_cred` field, 96 to 97
`rstat` program
multithreaded, 111 to 116
`run` configuration-script keyword, 319
`runwait` configuration-script keyword, 318 to 319
`rusers` routine, 60 to 63

S

SAC (service access controller)
described, 302 to 305
key files, 310, 315, 329
log file, 330
message interface, 306 to 309, 315, 321 to 327, 330
`sac.h` header file, 325 to 327
`sacadm` command, 106, 302, 310, 312 to 313, 319 to 320
`_sacpipe` file, 307, 315, 330
`_sactab` file, 310, 329
starting, 315, 317
`sac.h` header file, 325 to 327
`sacadm` command, 106, 302, 310, 312 to 313, 319 to 320
`_sacpipe` file, 307, 315, 330
`_sactab` file, 310, 329
SAF (service access facility), 301 to 330
administrative interface, 309 to 316, 319 to 321
key files, 315
monitor-specific command, 313 to 314
`pmadm` command, 105 to 106, 306, 311, 313, 320 to 321
`_pmtab` file, 306, 311 to 312, 315, 330
port monitor implementation requirements, 314 to 315
port monitor responsibilities, 315 to 316
`sacadm` command, 106, 302, 310, 312 to 313, 319 to 320
`_sactab` file, 310, 329
service interface, 314
configuration scripts, 316 to 321
installing, 319 to 321
language for writing, 318 to 319
per-port monitor, 315, 316, 317, 320, 330
per-service, 305, 306, 314, 315, 316, 317 to 318, 320 to 321, 330
per-system, 316, 317, 319 to 320, 329
printing, 319 to 321
replacing, 319 to 321
directory structure, 329 to 330
files used by, 306, 310, 311 to 312, 315
logic diagram, 327, 328
message interface, 306 to 309, 315, 321 to 327, 330
overview, 301 to 305
port monitor functions and, 303 to 305, 315 to 316
SAC (service access controller) and, 302 to 305, 306 to 309

sample code, 321 to 327
terminating port monitors, 305, 315
`sc_size` field, 307, 309
searching NIS+ tables, 154
security
See also access control; authentication
NIS+, 151
semantics
TI-RPC call, 12, 209
serializing, 30 to 35, 64 to 67, 134 to 135, 177 to 179, 181 to 182, 332
See also XDR (external data representation)
server handles
creating
bottom level interface, 15, 81 to 82
current vs. previous release, 139 to 140
expert level interface, 15, 79 to 80
intermediate level interface, 14, 74 to 75
top level interface, 14, 71 to 72
destroying, current vs. previous release, 139
low-level data structures for, 83 to 85
server programs
remote copy, 133 to 134
`rpcgen` tool and
broadcast call response, 50, 52
client authentication, 51, 54, 96 to 97
complex data structure passing, 32 to 33
C-style mode, 41
debugging, 56 to 57
directory listing service, 32 to 33, 282 to 283
MT Auto mode, 48
MT-safety, 22, 47 to 48
network type/transport selection, 50, 51
overview, 23, 29
simplified interface, 63
transient RPC program, 110
server stub routines
`rpcgen`, 21
rpcgen tool and, 21
`rpcgen` tool and, 23, 29
ANSI C-compliant, 49
MT Auto mode, 48
MT-safe, 22, 44 to 45
preprocessing directive, 36
server templates
`rpcgen` tool, 22, 37, 38, 41
server transport handle, 83 to 85
servers
See also registering
authentication and, 96 to 97, 98 to 99, 100 to 101
batched, 94 to 95, 292 to 293
caching, 82
crashes, 209, 223
defined, 332, 333
dispatch tables, 50, 55 to 56
exit interval, `rpcgen` tool and, 52 to 53
multiple versions, 106 to 108
multithreaded
Auto mode, 22, 37, 48, 117, 118, 119 to 122
overview, 111, 116 to 118
safety, 22, 44 to 45, 47 to 48, 59, 117, 332
unsafe routines, 117
User mode, 117, 118, 123, 127 to 130
NIS+, 150, 153, 155 to 156
`poll` routine and, 88 to 90
port monitors and, 104 to 106
transaction IDs and, 209
service access controller, *See* SAC (service access controller)
service access facility, *See* SAF (service access facility)
service transport handle (SVCXPRT), 104, 118
service-dispatch routine
authentication and, 96 to 97

`setnetconfig` routine, 78
signed integers
  XDR language, 253 to 254
simple declarations
  RPC language, 234
simplified interface routines (RPC), 13, 60 to 67
  client, 61 to 62
  hand-coded registration routine, 64
  MT safety of, 59
  overview, 13, 60
  routines not usable with, 68
  server, 63
  XDR conversion, 64 to 67
single-threaded mode
  as default, 117
  `poll` routine and, 88 to 90
socket functions, *See* TS-RPC (transport-specific remote procedure call)
SPARCompiler C++ 3.0
  `rpcgen` tool and, 49
`spray.x` (spray packets) program, 286 to 287
standard interface routines (RPC), 13 to 15, 68 to 85
  bottom level routines, 15, 80 to 82
  expert level routines, 15, 75 to 80
  intermediate level routines, 14, 73 to 75
  low-level data structures, 82 to 85
  MT safety of, 59
  server caching, 82
  top level routines, 14, 28 to 29, 68 to 72
standards
  ANSI C standard,, 23
  ANSI C standard, `rpcgen` tool and, 37, 49
  naming standard, 221
  record-marking standard, 217 to 218
  RPC, 10, 217 to 218
  XDR canonical standard, 179 to 180
statistics, *See* information reporting
status reporting, *See* information reporting
stream transports
  See also connection-oriented transports
  defined, 333
STREAMS modules
  port monitor configuration and, 318, 320
streams, *See* XDR (external data representation), streams
string declarations
  RPC language, 25, 239
  XDR language, 260 to 261
string representation
  XDR routines, 67, 187 to 188
structure declarations
  See also data structures
  RPC language, 31, 236
  XDR language, 263, 270 to 271
stub routines, *See* client stub routines; server stub routines
Sun RPC, *See* TI-RPC (transport-independent remote procedure call)
SunOS 5.x
  `rpcgen` tool features, 22 to 23
`_svc` suffix, 49
`_svc.c` suffix, 29
`svc_create` routine
  current vs. previous release, 140
  described, 14, 72
`svc_destroy` routine, 68, 139
`svc_dg_create` routine
  current vs. previous release, 140
  described, 15, 84
  using, 82
`svc_dg_enablecache` routine, 82
`svc_done` routine, 117, 123
`svc_fd_create` routine, 104 to 105, 140
`svc_freeargs` routine, 135
`svc_getargs` routine
  described, 135
  MT performance and, 120, 127
`svc_getcaller` routine, 140
`svc_getreqpoll` routine, 88, 117

svc_getreqset routine, 88, 117
svc_getrpccaller routine, 140
svc_pollset routine, 88
svc_raw_create routine, 85 to 87, 139, 140
svc_reg routine
  current vs. previous release, 140
  described, 15
  port monitors and, 104
svc_register routine, 140
svc_run routine
  bypassing, 88
  described, 63, 72
  multithreaded RPC servers and, 117
  poll routine and, 88, 89 to 90
svc_sendreply routine, 72
svc_tli_create routine
  current vs. previous release, 140
  described, 15, 79
  using, 79, 80, 104
svc_tp_create routine, 14, 139, 140
svc_udp_bufcreate routine, 139
svc_unreg routine, 15, 140
svc_unregister routine, 140
svc_vc_create routine
  current vs. previous release, 140
  described, 15, 84
  using, 82
svcerr_systemerr routine, 99
svcfd_create routine, 139
svctag file, 311 to 312, 315, 316, 330
svcudp_create routine, 79 to 80, 139
SVCXPRT service transport handle, 104, 118
svrerr_weakauth routine, 99
synchronization, *See* time synchronization
syntax
  RPC language, 231 to 232, 272
  XDR language, 269 to 270
, 320
_sysconfig file, 316, 317, 319 to 320, 329

T

tables (NIS+)
  access functions, 153, 154
  administration commands, 152
  overview, 150 to 151
  sample programs, 163 to 165
taddr2uaddr routine, 18
/tag directory, *See* /pmtag directory
TCP (transport control protocol)
  See also connection-oriented transports
  nettype parameter for, 16
  porting TCP applications from TS-RPC to TI-RPC, 136
  portmap port number for, 299
  portmap sequence for, 296 to 297
  RPC protocol and, 209
  rpcbind port number for, 19, 245
  server crashes and, 209
tcp transport type, 16
TCP/IP protocol, *See* TCP (transport control protocol)
TCP/IP streams
  XDR, 199 to 201, 217 to 218
templates
  rpcgen tool, 22, 37, 38, 39 to 41
terminating port monitors, 305, 315
testing
  NIS+ groups, 155
  programs using low-level raw RPC, 85 to 87
thr_create routine, 123
thread library
  lthread, 112
thread.h file, 123
threads, *See* MT Auto mode; MT User mode; MT-safe code; multithreaded RPC programming
time
  obtaining current, 141, 222, 247
  ping program, 230 to 231
time server program, 36, 48, 285

time service
intermediate level client for, 73 to 74
intermediate level server for, 74 to 75
`rpcbind` routine, 141, 222, 247
top level client for, 69 to 70
top level server for, 71 to 72
time synchronization
`AUTH_DES` authentication, 100, 222 to 223
`AUTH_KERB` authentication, 102, 229, 230
NIS+, 156
`time.x` program, 36, 48, 285
`time_prog` routine, 72
timed client creation
intermediate level interface, 14, 74
top level interface, 14, 70
time-out periods
`rpcgen` tool and, 51, 53
timestamps, *See* time synchronization
TI-RPC (transport-independent remote procedure call)
See also RPC (remote procedure call); `rpcgen` tool
address lookup services, 15, 18, 19
address registration, *See* `rpcbind` routine
address reporting, 20
address translation, 17 to 18, 19, 137
call semantics, 12
data representation, 12
described, 4, 9 to 10
identifying remote procedures, 12, 209, 210 to 213
information reporting, 20, 109 to 110
interface routines, 13 to 15, 59 to 82
bottom level, 15, 80 to 82
caching servers, 82
expert level, 15, 75 to 80
intermediate level, 14, 73 to 75
low-level data structures, 82 to 85
overview, 13 to 15, 59 to 60, 68
simplified, 13, 60 to 67, 68
standard, 13 to 15, 68 to 85
top level, 14, 28 to 29, 68 to 72
library selection, `rpcgen` tool and, 23, 37, 49
name-to-address translation, 17 to 18, 19, 137
network selection, 16
parameter passing, *See* arguments
protocol, 207 to 218
See also RPC language (RPCL)
authentication and, 211 to 212
binding and rendezvous independence and, 11, 210
identifying procedures, 12, 209, 210 to 213
in XDR language, 214 to 217
overview, 207 to 209
record-marking standard, 217 to 218
transport protocols and semantics and, 11, 12, 209
version number, 211
raw, testing programs using low-level, 85 to 87
transient RPC program numbers, 109 to 110, 212
transport selection, 17 to 18
transport types, 16
TS-RPC and, *See* porting TS-RPC to TI-RPC
TLI (transport-level interface), *See* expert level interface routines
TLI file descriptors
passing open, 76, 79
top level interface routines (RPC), 14, 28 to 29, 68 to 72
client, 28 to 29, 68 to 70
overview, 14, 68
server, 71 to 72
transaction IDs, 12, 209
transaction log functions (NIS+), 153, 156
transient program numbers, 109 to 110, 212
translating, *See* converting

transport
defined, 333
transport addresses (netbuf addresses), 18, 247
transport handles
defined, 333
server, 83 to 85
SVCXPRT service, 104, 118
XDR routines requiring, 68
transport protocols
See also TCP (transport control protocol); UDP (user datagram protocol)
RPC protocol and, 209
transport selection
RPC, 17 to 18
rpcgen tool, 50, 51
transport types
See also connection-oriented transports; connectionless transports
described, 16, 17
interfaces and, 68
rpcgen tool and, 50, 51
transport-independent remote procedure call, *See* TI-RPC (transport-independent remote procedure call)
transport-level interface (TLI) routines, *See* expert level interface routines
transport-level interface file descriptors
passing open, 76, 79
transport-specific remote procedure call, *See* TS-RPC (transport-specific remote procedure call)
trees, 266
TS-RPC (transport-specific remote procedure call)
library selection, rpcgen tool and, 37, 49
porting to TI-RPC, *See* porting TS-RPC to TI-RPC
ttyadm command, 306
ttymon port monitor, 306
tutorials
, 23, 37
type definitions
RPC language, 233
XDR language, 265 to 266, 270

U

uaddr2taddr routine, 18
UDP (user datagram protocol)
See also datagram transports
broadcast RPC and, 90
client creation routines for, 76 to 78, 81
nettype parameter for, 16
porting UDP applications from TS-RPC to TI-RPC, 136
portmap port number for, 299
RCP protocol and, 209
rpcbind port number for, 19, 245
server creation routines for, 79 to 80, 81 to 82
udp transport type, 16
UDP/IP protocol, *See* UDP (user datagram protocol)
ulimit command, 319
umask command, 319
unions
declarations
RPC language, 31, 236 to 237
XDR language, 263 to 264, 266, 270
XDR code samples, 194 to 196
universal addresses, 17 to 18, 246, 247, 296, 333
unregistering
See also registering
current vs. previous release, 140
portmap routine, 299
rpcbind routine, 18, 243, 246
rpcinfo routine, 20
unsigned hyper integers
XDR language, 255 to 256
unsigned integers

XDR language, 254
user datagram protocol, *See* UDP (user datagram protocol)
User MT mode, 117, 118, 123 to 130
user's bind address
passing, 79
users
number of
on a network, 98 to 99
on a remote host, 60
`/usr/include/rpcsvc` directory, 213
`/usr/share/lib` directory, 35
`utmp` entries
creating, 305, 312, 316

V

`/var/saf/_log` file, 330
`/var/saf/pmtag` directory, 306, 311, 330
variable declarations, 234
variable-length array declarations
See also arrays
RPC language, 235
XDR language, 262
variable-length opaque data
See also opaque data
XDR language, 259 to 260
verifiers
`AUTH_DES`, 221 to 222, 224 to 225
`AUTH_KERB`, 103, 104, 228, 229 to 230
`AUTH_SYS`, 219 to 220
described, 211 to 212
version numbers
See also program numbers; versions
assigning, 106
changing, 106
described, 12, 106, 210
error conditions, 211
mapping, *See* `portmap` routine; `rpcbind` routine
message protocol, 211
multiple client versions, 108 to 109
multiple server versions, 106 to 108
port monitors, 312, 313 to 314
registration of, 106
version-lists
RPC language, 232
versions
See also version numbers
library functions, compatibility of current vs. previous release, 139 to 142
RPC language, 232
`visible` transport type, 16
`void` arguments, 238
void declarations
RPC language, 240
XDR language, 264

W

window of credentials
`AUTH_DES` authentication, 100, 223 to 224
`AUTH_KERB` authentication, 102, 229
defined, 222
window verifiers, 222

X

`x_base` field, 202
`x_destroy` macro, 202
`x_getbytes` routine, 202
`x_getlong` routine, 202 to 203
`x_getpostn` macro, 202
`x_handy` field, 202
`x_inline` routine, 202
x_op, 198
`x_op` field, 202
`x_private` field, 202
`x_public` field, 202
`x_putbytes` routine, 202
`x_putlong` routine, 202 to 203
`x_setpostn` macro, 202
`.x` suffix, 32
XDR (external data representation), 175 to 206

See also XDR language
block size, 252
canonical standard, 179 to 180
converting from (deserializing), 64, 67, 72, 134, 135, 181 to 182, 331
converting to (serializing), 30 to 35, 64 to 67, 134 to 135, 177 to 179, 181 to 182, 332
cost of conversion, 179 to 180
described, 4, 175 to 179, 251
direction determination for operations, 198
direction independence of routines, 181
file data structure in, 270 to 271
graphic box notation, 252
library, 180 to 182
  See also XDR (external data representation), primitive routines
linked lists, 203 to 206, 266
memory allocation with, 134 to 135
optimizing routines, 198
primitive routines, 65 to 67, 181, 182 to 201
  arrays, 189 to 192, 193 to 194
  byte arrays, 189
  constructed (compound) data type filters, 66 to 67, 187
  discriminated unions, 194 to 196
  enumeration filters, 186 to 187
  fixed-length arrays, 193 to 194
  floating point filters, 65, 186
  memory requirements, 183 to 185, 187
  no-data routine, 187
  nonfilter, 198
  number filters, 65 to 66, 185 to 186
  opaque data, 192 to 193
  overview, 182
  pointers, 196 to 197
  strings, 67, 187 to 188
  unions, 194 to 196
protocol, *See* XDR language
remote copy (two-way XDR) routine, 131 to 134
`rpcgen` tool and, 30 to 35, 36, 175
streams
  accessing, 198
  creation by RPC system, 180
  implementing new instances of, 201 to 203
  interface to, 201 to 203
  memory, 199
  nonfilter primitives for, 198
  record (TCP/IP), 199 to 201, 217 to 218
  standard I/O, 199
transport handles and, 68
XDR language, 253 to 271
arrays, 261 to 262, 270
`AUTH_DES` authentication protocol in, 223 to 226
booleans, 255
comments, 267
constants, 265, 267, 270
counted byte strings, 260 to 261
declarations, 253 to 266
discriminated unions, 263 to 264, 266, 270
enumerations, 254 to 255
file data structure described in, 270 to 271
fixed-length arrays, 261 to 262
fixed-length opaque data, 258 to 259
floating point, 256 to 258
hyper integers, 255 to 256
identifiers, 267
integers, 177 to 178, 253 to 254, 255 to 256
keywords, 269
opaque data, 258 to 260
optional-data unions, 266
overview, 251 to 252, 333
quadruple-precision floating point, 257 to 258
RPC language vs., 230, 232, 272
RPC message protocol in, 214 to 217
signed integers, 253 to 254

specification for, 267 to 271
strings, 260 to 261
structures, 263, 270 to 271
syntax, 269 to 270
type definitions, 265 to 266, 270
unions, 263 to 264, 266, 270
unsigned hyper integers, 255 to 256
unsigned integers, 254
variable-length arrays, 262
variable-length opaque data, 259 to 260
voids, 264
xdr_ prefix, 32
xdr_array routine, 66, 189 to 192, 196
xdr_bool routine, 65
xdr_bytes routine, 66, 67, 189
xdr_char routine, 65, 185
xdr_chararr routines, 134 to 135
xdr_cnd routine, 192
XDR_DECODE operation, 187
xdr_destroy routine, 198
xdr_double routine, 65, 186
xdr_element routine, 190
XDR_ENCODE operation, 187
xdr_enum routine, 65
xdr_float routine, 65, 186
XDR_FREE operation, 187
xdr_free routine, 35, 45
xdr_getpos routine, 198
xdr_gnumbers routine, 181 to 182, 203 to 206
xdr_history routine, 192
xdr_inline count, 37, 50
xdr_int routine, 65, 185
xdr_long routine, 65, 177 to 178, 181, 185
xdr_netobj routine, 65, 193
xdr_opaque routine, 66, 192
xdr_party routine, 191
xdr_pgn routine, 197
xdr_pointer routine, 66, 197, 204 to 205, 206
xdr_quadruple routine, 65
xdr_rcp routine, 131 to 134, 143
xdr_reference routine, 66, 67, 196 to 197, 206
xdr_setpos routine, 198
xdr_short routine, 65, 186
xdr_simple routine, 65, 67
xdr_sizeof routine, 183 to 185
xdr_string routine, 65, 66, 67, 188, 191, 192
xdr_type(object) notation, 103
xdr_u_char routine, 65, 185
xdr_u_int routine, 65, 185
xdr_u_long routine, 65, 186
xdr_u_short routine, 65, 186
xdr_union routine, 66, 194 to 196
xdr_varintarr routine, 66
xdr_vector routine, 66 to 67, 193 to 194
xdr_void routine, 65, 187
xdr_wrapstring routine, 65, 191, 192
xdrmem_create routine, 199
xdrrec_create routine, 200
xdrrec_endofrecord routine, 200 to 201
xdrrec_eof routine, 201
xdrrec_skiprecord routine, 201
xdrstdio_create routine, 180, 199
xp_fd field, 84
xp_ltaddr field, 84
xp_netid field, 84
xp_rtaddr field, 84
xp_tp field, 84
xprt_register routine, 140
xprt_unregister routine, 140