Index

Symbols

.Xauthority file 97–98

A

Adobe FTP site 23

Adobe public access file server 23

authorization protocols, *See* security

authorization-based access control mechanism, *See* security

B

bdftopcf 46

bitmap distribution format 46

bitmap fonts 46–47, 52

Black pixel location note 14

bus, used in SPARCsystems 127

BW2 display device, description of 102
  See also display devices

C

CG3 display device, description of 103
  See also display devices

CG6 display device, *See* GX display device and GXplus display device

CG8 display device, *See* TC display device

client
  running locally as another user 100
  running remotely 100

client library
  for DPS 18

color
  color name database 14
  recommendations 14

compose key support 13

compressing font files 47

contexts
  and DPS 18
  secure 21
  three ways to share VM 21

D

DES (Data Encryption Software), with SUN-DES-1 95

display devices
  bus, used in Sun SPARCsystems 127
  BW2

description of 102
CG3
description of 103
CG6, *See* GX and GXplus
CG8, *See* TC
GT
window damage note 103
GX
description of 103
GXplus
description of 103
programming hints 37
supported devices table 102
TC
description of 103
DISPLAY environment variable 100
DPS
.upr files 50
changing the resource path 50
client library 18
font enhancements 20
libraries supported 20
PostScript interpreter 18
pswrap translator 18
security issues 21

F

F3 fonts 47
character set supported by 55
F3BitMap resource 47
font management library, definition of 3
fonts
.afm file 45
.enc file 45, 55
.map file 45
.ps file 45
.trans file 45
.upr file 45, 53
adding bitmap fonts 52
adding new fonts 51–56
adding scalable fonts 53, 56
and X terminals 56
default font path in X11 48
files included in openwindows 45
fonts.alias file 52, 55
fonts.dir file 52
fonts.scale file 54
formats 44–45
outline and bitmap 46, 47
replacing outline with bitmap 47
using F3 fonts 47
ftp program 4
ftp, accessing Adobe FTP site 23

G

GX display device, description of 103
See also display devices
GXplus display device, description of 103
See also display devices

H

host-based access control mechanism, *See* security

L

libraries
DPS. list of 20
X, list of 8

M

makebdf 46
makepsres 53

MBX (multi-buffering) X extension 5
MIT-MAGIC-COOKIE-1 authorization protocol, *See* security
MIT-SHM (Shared Memory) X extension 5
mkfontdir 52
multiple plane group, characteristics of 37

N

NISdomainname, definition of 98

O

openwin command
  -noauth option 94, 96
outline fonts 46, 47
overlay windows
  advanced features
    background 61
    backing store 62
    border 62
    choosing visuals 65–66
    colormap 63
    gravity 63
    input distribution model 63
    print capture 64–65
  and existing pixel transfer routines 81–82
  and existing primitive rendering routines 71–72
  basic features
    creation 68
    definition 59–70
    viewability 60

P

portable compiled format 46
  compressed files 47
PostScript interpreter 18
pswrap translator 18

R

resource files (.upr) 50
RPC (Remote Procedure Call), with SUN-DES-1 95

S

scalable fonts 53–56
secure context creation 21
security 93–100
  .Xauthority file 97–98, 99
    contents with MIT-MAGIC-COOKIE-1 98
    contents with SUN-DES-1 98
  access control mechanisms 94–95
    definition of 94
    how both are active 97
  authorization protocols 95–96
    default configuration 95
    default, how to change 96
  authorization-based, *See* user-based clients
    running locally as another user 100
    running remotely 100
  connection attempt error message 94
  default configuration 95
  determining if configuration change is required 93
  host-based, backward compatibility 94
  host-based, definition of 94
  MIT-MAGIC-COOKIE-1 authorization protocol 95
  NISdomainname, definition of 98

-noauth option 94
weakens security warning 96
server
manipulating access 97–100
allowing access with MIT-MAGIC-COOKIE-1 99
allowing access with SUN-DES-1 99
SUN-DES-1 authorization protocol
definition of 95–96
need to reconfigure 93
user-based, definition of 94
userid, definition of 98
xauth program 97, 99
xhost program 99
server
applications that run with 8
architecture diagram 3
changing X11 default font path 48–49
DIX layer, definition of 3
font management library, definition of 3
manipulating access control 97–100
OS layer, definition of 3
SHAPE X extension 5
SUN-DES-1 authorization protocol, *See* security
system file access 21

T

TC display device, description of 103
See also display devices

U

user-based access control mechanism, *See* security

V

virtual memory 18
visuals
default
get with XGetVisualInfo function 36
gamma-corrected 38–42
multiple plane group, characteristics of 37
VM (virtual memory) 18, 21
shared 18

W

White pixel location note 14

X

X
applications not supported 10
applications supported 9
compose key 13
extensions
MBX (multi-buffering) 5
MIT-SHM (Shared Memory) 5
SHAPE 5
XInput 5
XTEST 6
libraries supported 8
terminals and fonts 56
X Consortium
extensions supported 4
xauth program 97, 99
XCopyArea, and overlay windows 82
XCopyPlane, and overlay windows 82
XDPSCreateSecureContext 22
XGetImage, and overlay windows 81
XGetVisualInfo function

list default visual 36
xhost program 99
XInput X extension 5
XLFD
font naming convention 54
xlsfonts 52, 55
XOvlSelectPair 88
XSetFontPath 49
XTEST X extension 6