Index

A

addresses, 22
`.alias`, 45
`.align`, 45
`as` command, 59
`.ascii`, 45
`.asciz`, 45
assembler command line, 59
assembler command line options, 60
assembler directives, 24
    types, 24
assembly language, 3
    lines, 4
    statements, 4
    syntax notation, 3
assignment directive, 25
`atof(3)`, 5, 46, 49

B

binary operations, 9
`.byte`, 45
byte order for V9, 73

C

case distinction, 4
case distinction, in special symbols, 8
cc language driver, 59
command-line options, 60
comment lines, 5
comment lines, multiple, 5
`.common`, 46
constants, 5
    decimal, 5
    floating-point, 5
    hexadecimal, 5
    octal numeric, 5
Control Transfer Instructions (CTI), 10
converting existing object files, 27
coprocessor instruction, 40
`cp_disabled` trap, 40
`cp_exception` trap, 41
current location, 21
current section, 14

D

`-D` option, 60
data generating directives, 25
default output file, 11
`dis` program, 63
disassembling object code, 63
`.double`, 46

E

ELF header, 12 to 13
    ehsize, 12
    entry, 12
    flag, 12
    ident, 12
    machine, 12
    phentsize, 13
    phnum, 13
    phoff, 13
    shentsize, 13
    shnum, 13
    shoff, 13
    shstrndx, 13
    type, 13
    version, 13
`.empty`, 46
.empty pseudo-operation, 10
error messages, 10
escape codes, in strings, 6
Executable and Linking Format (ELF) files, 2, 11
expressions, 9

F

f77 language driver, 59
`fbe` command, 59
features, lexical, 4
`.file`, 46
file syntax, 4
floating-point instructions, 39
floating-point pseudo-operations, 5

G

`.global`, 47
`.globl`, 47

H

`.half`, 47
hardware instructions
    SPARC architecture, 29
hardware integer
    assembly language instructions, 31
hyphen (-), 59

I

`-I` option, 60
`.ident`, 47
instruction set changes (V9), 74
instruction set extensions (V9), 89
instruction set, used by assembler, 29
instructions
    assembly language, 31
    hardware integer, 31
integer instructions, 31
integer suffixes, 5
invoking, `as` command, 59

K

`-K` option, 60

L

`-L` option, 61
labeling format, 2
labels, 5
language drivers, 59
lexical features, 4
lines syntax, 4
`.local`, 47
location counter, 21
locations, 21

M

`-m` option, 61
multiple comment lines, 5
multiple files, on *as command line*, 59
multiple sections, 15
multiple strings
    in string table, 24

N

.noalias, 48
.noalias pseudo-op, 45
.nonvolatile, 48
numbers, 5
numeric labels, 5

O

-o option, 61
object file format, 2
object files
    type, 2, 11
operators, 9
.optim, 48
options
    command-line, 60

P

-P option, 61
percentage sign (%), 7
.popsection, 48
predefined non-user sections, 20
predefined user sections, 19
.proc, 48
pseudo-operations, 45
pseudo-ops
    examples of, 55
.pushsection, 48

Q

-Q option, 61
-q option, 61
.quad, 49

R

references, xii
registers, 7
relocatable files, 2, 11
relocation tables, 22
.reserve, 49

S

-S option, 61
-s option, 62
-sb option, 60
.section, 49
section control directives, 25
section control pseudo-ops, 25
section header, 15 to 18
    addr, 15
    addralign, 15
    entsize, 15
    flags, 16
    info, 16
    link, 16
    name, 16
    offset, 16
    size, 16
    type, 17
sections, 14
.seg, 50
.single, 50
.size, 51
.skip, 51
SPARC-V9, 71
    8-bit format, 89
    alternate space access, 73
    byte order, 73
    fixed data formats, 89
    floating-point instructions, 85
    graphics data formats, 89
    instruction set changes, 74
    instruction set extensions, 89
    instruction set mapping, 77
    registers, 72
    synthetic instruction set, 87
special floating-point values, 5
special names, floating point values, 5
special symbols, 7
.stabn, 51
.stabs, 51

statement syntax, 4
string tables, 24
strings, 6
    multiple in string table, 24
    multiple references in string table, 24
    suggested style, 6
    unreferenced in string table, 24
sub-strings in string table
    references to, 24
`symbol`, 53
symbol attribute directives, 25
symbol names, 6
symbol table, 22 to 23
    info, 23
    name, 22
    other, 23
    shndx, 23
    size, 23
    value, 22
symbol tables, 22
syntax notation, 3
synthetic instructions, 41

T

`-T` option, 62
table notation, 30
trap numbers, reserved, 37
`.type`, 51

U

`-U` option, 62
`.uahalf`, 51
`.uaword`, 51
unary operators, 9
user sections, 25
`/usr/include/sys/trap.h`, 37

V

`-V` option, 62
`.version`, 52
`.volatile`, 52

W

`.weak`, 52
`.word`, 52

X

`-xarch=v7` option, 62
`-xarch=v8` option, 62
`-xarch=v8a` option, 63
`-xarch=v8plus` option, 63
`-xarch=v8plusa` option, 63
`.xstabs`, 52