Index

A

ALE (Asian language environment), 137
API for internationalization, 41
API summaries, 81
ASCII, 22, 25, 28
Asian characters, 28
Asian input procedure, 32
attributes
    naming conventions, 29
    new or modified, 122
    obsolete, 122

B

back-end input method, 37, 137
buf_len, 120

C

C locale display, 135
callback function, 137
canvas
    input context, 42
    input method, 42
    joining views, 10
    package, 41
CANVAS_IM_PREEDIT_FRAME, 42, 81, 122
character display, and non-internationalized XView applications, 135
character encoding
    ASCII, 22, 25, 28
    Asian characters, 28
    Compound Text, 25
    EUC, 22, 25
    in XView, 22
    ISO Latin-1, 21, 25, 51
character, definition, 137
Chinese
    input methods, 32
    simplified, xvi
    traditional, xvi
CLE (Chinese language environment), xvi, 137
client-displays, 39, 78
CMS_COLOR_COUNT
    corrections to XVRM, 9
code set, definition, 138
codepoint, definition, 138
compatibility, XView 3.3 and earlier versions, 25, 115
Compiling XView 3.3 Programs, 23
Compound Text, 25
container classes
    and XView panels, 15

cursor package, 42
CURSOR_STRING_WCS, 42, 81, 122

D

defaults_get_locale(), 109, 122
defaults_set_locale(), 109, 122
drag and drop
    Motif and XView interoperability, 4

E

encoding
    ASCII, 22, 25, 28
    Asian characters, 28
    Compound Text, 25
    EUC, 22, 25
    in XView, 22
    ISO Latin-1, 21, 25, 51
explicit commit, definition, 138
Extended UNIX Code (EUC), 22, 25, 138

F

file chooser package, 43
file list package, 44
FILE_CHOOSER_APP_DIR_WCS, 43, 82, 123
FILE_CHOOSER_CUSTOMIZE_OPEN_WCS, 43, 82, 123
FILE_CHOOSER_DIRECTORY_WCS, 43, 82, 123
FILE_CHOOSER_DOC_NAME_WCS, 43, 82, 123
FILE_CHOOSER_FILTER_STRING_WCS, 43, 83
FILE_CHOOSER_FILTER_WCS, 123
FILE_CHOOSER_NOTIFY_FUNC_WCS, 43, 83, 123
FILE_CHOOSER_WCHAR_NOTIFY, 43, 83, 123
FILE_LIST_DIRECTORY_WCS, 44, 83, 123
FILE_LIST_DOTDOT_STRING_WCS, 44, 84, 123
FILE_LIST_FILTER_STRING_WCS, 44, 84, 123
FILE_LIST_WCHAR_NOTIFY, 44, 84, 123
focus follows mouse
    XView and Motif interoperability, 5
font
    compatibility issues, 51
    glyph fonts, 50
    package, 45
    portability issues, 52
    set, definition, 50
    sets, 23, 45, 129 to 131
FONT_CHAR_HEIGHT_WC, 46, 84, 123
FONT_CHAR_WIDTH_WC, 46, 84, 123
FONT_COLUMN_WIDTH, 46, 85, 123
FONT_LOCALE, 46, 47, 85, 123
FONT_NAMES, 46, 47, 85, 123
FONT_SET_ID, 46, 48, 85, 123
FONT_SET_SPECIFIER, 46, 49, 85, 123
FONT_STRING_DIMS_WCS, 46, 86, 123
frame package, 52
    changes, 116
FRAME_LABEL_WCS, 52, 86, 123
FRAME_LEFT_FOOTER_WCS, 52, 86, 123
FRAME_RIGHT_FOOTER_WCS, 52, 86, 123
front-end input method, 37, 139
functions
    naming conventions, 29
    new or modified, 122

G

glyph fonts, 50

H

history package, 53
HISTORY_ADD_FIXED_ENTRY_WCS, 53, 87, 123

HISTORY_ADD_ROLLING_ENTRY_WCS, 53, 87, 123
HISTORY_LABEL_WCS, 53, 87, 123
HISTORY_NOTIFY_PROC_WCS, 53, 87, 123
HISTORY_VALUE_WCS, 53, 87, 123
HLE (Hanyu language environment), xvi, 139

I

IC (input context), 74
ICCCM, 139
icon package, 53
ICON_LABEL_WCS, 53, 88, 123, 124, 125, 126, 127
ICON_TRANSPARENT_LABEL_WCS, 53, 88, 123
ideogram, definition, 139
IM (input method) server, 37, 139
implicit commit, 38, 57, 75
  definition, 139
input context (IC), 74
input method, 31 to 39
  architecture, 36
  callback procedures, 78
  choosing the input style, 74
  customizing, 39
  definition, 23, 31
  determining style, 35
  enabling and disabling, 36, 72
  IM server, 37, 139
  preedit styles, 34
  screen regions, 32
  status, 140
  status styles, 34
input style, 140
internationalization features, 41
interoperability
  focus follows mouse and Motif, 5
  Motif and XView drag and drop, 4
  Motif and XView selections, 3
  window decoration, 4
  XView client with two base windows, 4
  XView text editor and Motif, 4
ISO Latin-1, 21, 25, 51

J

Japanese writing systems, 31
JFP (Japanese Feature Package), xvi, xviii
JLE (Japanese language environment), 140
joining canvas views, 10

K

KLE (Korean language environment), xvi, 140
Korean writing systems, 32

L

layout, object, 22
locale setting, 22
lookup choice region, 32, 141

M

menu package, 53
MENU_ACCELERATOR_WCS, 54, 88, 124
MENU_ACTION_ACCELERATOR_WCS, 54, 88, 124
MENU_ACTION_ITEM_WCS, 54, 89, 124
MENU_GEN_PIN_WINDOW_WCS, 54, 89, 124
MENU_GEN_PROC_ITEM_WCS, 54, 89, 124
MENU_GEN_PULLRIGHT_ITEM_WCS, 54, 89, 124
MENU_PULLRIGHT_ITEM_WCS, 54, 90, 124
MENU_STRING_ITEM_WCS, 54, 90, 124
MENU_STRING_WCS, 54, 90, 124

MENU_STRINGS_AND_
ACCELERATORS_WCS, 54, 91, 124
MENU_STRINGS_WCS, 54, 90, 124
MENU_TITLE_ITEM_WCS, 54, 91, 124
meta key alternatives, x86, meta key alternatives, xvii
Motif Window Manager, 3
multibyte character, 22 to 23, 25

N

naming conventions for attributes and functions, 29
non-internationalized XView applications, 8-bit character display, 135
notice package, 54
notice.c, 8
NOTICE_BUTTON_NO_WCS, 54, 91, 124
NOTICE_BUTTON_WCS, 54, 91, 124
NOTICE_BUTTON_YES_WCS, 54, 92, 124
NOTICE_MESSAGE_STRING_WCS, 54, 92, 124
NOTICE_MESSAGE_STRINGS_ARRAY_PTR_WCS, 54, 92, 124
NOTICE_MESSAGE_STRINGS_WCS, 54, 92, 124
notify.h header file, 135
notify_next_event_func
corrections to XVPM, 8
numeric text fields
and PANEL_EVENT_PROC, 15
and PANEL_ITEM_OWNER, 15

O

object layout, 22
obsolete attributes, 122
on-the-spot, 39, 42, 78
OPEN LOOK Mouseless Specification, 11

P

package changes, 116 to 122
panel package, 54
changes, 116
PANEL_CHOICE_STRING_WCS, 55, 93, 124
PANEL_CHOICE_STRINGS_WCS, 55, 93, 124
PANEL_CLIENT_DATA attribute, 15
PANEL_EVENT_PROC
and numeric text fields, 15
corrections to XVPM, 8
panel_get_value_wcs, 55, 109, 125
PANEL_ITEM_IC_ACTIVE, 55, 56, 93, 124
PANEL_ITEM_OWNER attribute, 15
PANEL_LABEL_STRING_WCS, 55, 93, 124
PANEL_LIST_INSERT_STRINGS_WCS, 55, 94, 124
PANEL_LIST_ROW_VALUES_WCS, 55, 57, 94, 124
PANEL_LIST_STRING_WCS, 55, 94, 124
PANEL_LIST_STRINGS_WCS, 55, 95, 124
PANEL_LIST_TITLE_WCS, 55, 95, 124
PANEL_MASK_CHAR_WC, 55, 57, 95, 124
PANEL_MAX_TICK_STRING_WCS, 55, 96, 124
PANEL_MAX_VALUE_STRING_WCS, 55, 96, 124
PANEL_MIN_TICK_STRING_WCS, 55, 96, 124
PANEL_MIN_VALUE_STRING_WCS, 55, 97, 124
PANEL_NOTIFY_PROC_WCS, 55, 97, 116, 117, 124, 125, 126, 127
PANEL_NOTIFY_STRING_WCS, 55, 97
panel_set_value_wcs, 55, 109, 125
PANEL_VALUE_DISPLAY_LENGTH, 55, 98, 116, 125
PANEL_VALUE_STORED_LENGTH, 98, 116, 125

PANEL_VALUE_STORED_LENGTH_WCS, 55, 99, 125
PANEL_VALUE_WCS, 55, 98, 125
parent container object
  and using the child handle, 16
PATH_LAST_VALIDATED_WCS, 58, 99, 125
PATH_RELATIVE_TO_WCS, 58, 99, 125
pathname package, 57
performance, text subwindows, 66
preedit
  definition, 141
  region, 32
  styles, 34
  text, implicit commit, 38

S

screen regions for input, 32
SCROLLBAR_COMPUTE_SCROLL_PROC, 11 to 13
  attribute function, 11
  example function call, 11
SCROLLBAR_MOTION, 14 to 15
SCROLLBAR_NORMALIZE_PROC, 13 to 14
  attribute function, 13
  example function call, 13
selections, 61
  Motif and XView interoperability, 3
seln.c program
  corrections to XVPM, 7
SELN_REQ_CHARSIZE, 61, 99, 125
SELN_REQ_CONTENTS_WCS, 61, 100, 125
SELN_REQ_FIRST_WC, 61, 100, 125
SELN_REQ_LAST_WC, 61, 100, 125
server image package, 62
SERVER_IMAGE_BITMAP_FILE_WCS, 62, 100, 125
status
  region, 33
  styles, 34

T

text subwindows
  buffer, index, length API, 63
  Extras Menu, 70
  filename API, 64
  implicit commit, 69
  index adjustments, 65
  invalid data, 65, 68
  package changes, 117
  performance, 66
  programming considerations, 64
  wide character API, 66
TEXTSW, 119
TEXTSW_ACTION_CHANGED_DIRECTORY_WCS, 64, 101, 125
TEXTSW_ACTION_EDITED_FILE_WCS, 64, 101, 125
TEXTSW_ACTION_LOADED_FILE_WCS, 64, 101, 125
textsw_add_mark(), 118, 125, 126
textsw_add_mark_wc(), 63, 110, 118, 125
textsw_append_file_name_wcs(), 64, 110, 125
TEXTSW_CONTENTS, 63, 65, 118, 125
TEXTSW_CONTENTS_WCS, 101, 119, 125
textsw_delete(), 118, 125
textsw_delete_wcs(), 63, 110, 118, 125
textsw_edit(), 118, 126
textsw_edit_wcs(), 63, 110, 118, 126
textsw_erase(), 118, 126
textsw_erase_wcs(), 63, 111, 118, 126
TEXTSW_FILE_CONTENTS_WCS, 64, 102, 125
TEXTSW_FILE_WCS, 64, 102, 125
textsw_find_bytes(), 65, 118, 121, 126
textsw_find_mark(), 63, 118, 126
textsw_find_mark_wc(), 111, 118
textsw_find_mark_wcs(), 126
textsw_find_wcs(), 63, 111, 119
TEXTSW_FIRST, 118, 125
TEXTSW_FIRST_WC, 63, 102, 118, 125

textsw_index_for_file_line(), 118, 126
textsw_index_for_file_line_wc(), 63, 112, 118, 126
textsw_insert(), 65, 118, 120, 126
TEXTSW_INSERT_FROM_FILE_WCS, 64, 103, 125
textsw_insert_wcs(), 63, 112, 119, 126
TEXTSW_INSERTION_POINT, 118, 125
TEXTSW_INSERTION_POINT_WC, 63, 103, 118, 125
TEXTSW_LENGTH_WC, 63, 103, 119, 125
textsw_mark_wcs, 126
textsw_match_bytes(), 65, 118, 121, 126
textsw_match_wcs(), 63, 112, 119, 126
textsw_normalize_view(), 118, 126
textsw_normalize_view_wc(), 63, 112, 118, 126
textsw_possibly_normalize(), 118, 126
textsw_possibly_normalize_wc(), 63, 113, 118, 126
TEXTSW_READ_ONLY, 70
textsw_replace_bytes(), 65, 118, 120, 126
textsw_replace_wcs(), 63, 113, 119, 126
textsw_set_selection(), 118
textsw_set_selection_wcs(), 63, 113, 118, 126
textsw_store_file_wcs(), 64, 114, 126
TTY subwindow package, 71
ttysw_input_wcs(), 71, 114, 126
ttysw_output_wcs(), 71, 114, 126

W

wide character, 22, 23
  naming conventions
    attributes, 29
    functions, 29
  representation, 25
WIN_ERROR_MSG_WCS, 72, 103, 126
WIN_IC, 72, 103, 126
WIN_IC_ACTIVE, 72, 104, 126
WIN_IC_COMMIT_STRING, 72, 104
WIN_IC_COMMIT_STRING_WCS, 72, 126
WIN_IC_COMMIT_WCS, 104, 126
WIN_IC_COMMMIT_STRING, 126
WIN_IC_CONVERSION, 72, 104, 126
WIN_IC_PREEDIT_CARET, 72, 78, 105, 126
WIN_IC_PREEDIT_DONE, 72, 78, 105, 122, 126
WIN_IC_PREEDIT_DRAW, 72, 78, 105, 122, 126
WIN_IC_PREEDIT_START, 72, 78, 105, 122, 126
WIN_IC_RESET, 72, 106, 127
WIN_IC_STATUS_DONE, 72, 78, 106, 122, 127
WIN_IC_STATUS_DRAW, 72, 78, 106, 122, 127
WIN_IC_STATUS_START, 72, 78, 107, 122, 127
WIN_IM_*, 121
WIN_IM_LUC_DONE, 122, 127
WIN_IM_LUC_DRAW, 122, 127
WIN_IM_LUC_PROCESS, 122, 127
WIN_IM_LUC_START, 122, 127
WIN_IM_PREEDIT_DONE, 122
WIN_IM_PREEDIT_DRAW, 122
WIN_IM_PREEDIT_START, 122
WIN_IM_STATUS_DONE, 122
WIN_IM_STATUS_DRAW, 122
WIN_IM_STATUS_START, 122
WIN_USE_IM, 36, 70, 72, 107, 127
WIN_X_IM_STYLE_MASK, 72, 107, 127
window decoration
  XView and Motif interoperability, 4
window package changes, 120, 121

X

Xlib preedit styles, 34
Xlib status styles, 34
Xv_focus_rank, 10

XV_FOCUS_RANK attribute, 16
XV_HELP_DATA, 10
XV_IM, 72, 108, 127
XV_IM_STYLES, 35, 72, 108
XV_KEY_DATA attribute, 15
XV_LABEL_WCS, 52, 53, 108, 127
XView client
    interoperability with Motif, 3 to 4
    interoperability with Motif window manager, 4 to 5
    text editor in Motif environment, 4
    with two base windows, 4
XView panels
    and container classes, 15
XVPM corrections
    notify_next_event_func, 8
    PANEL_EVENT_PROC, 8
    seln.c program, 7
XVRM corrections
    CMS_COLOR_COUNT, 9