Index

Symbols

$OPENWINHOME/li, 201
$OPENWINHOME/lib/openwin-sys, 199
() function, 64
, tt, 198
/etc/inet/inetd.conf, 199
/usr/openwin/bin, 198
tt_message_user, 64
_SUN_TT_ARG_TRACE_WIDTH, 32
_SUN_TT_FILE, 32
_SUN_TT_HOSTNAME_MAP, 32, 38
_SUN_TT_PARTITION_MAP, 32, 39
_SUN_TT_SESSION, 16, 32, 65, 200, 201, 202
_SUN_TT_TOKEN, 32, 201
_sun_tt_token, 217

A

accessing ToolTalk data from machines not running a ToolTalk database server, 37
accessing ToolTalk databases, 57
adding a message pattern callback, 95
adding callbacks to static patterns, 89
adding files to scoped patterns, 26
adding inter-operability functionality, 160
adding ToolTalk code, 166
  Xedit files, 166
  Xfontsel files, 174
adding values to spec properties, 132
address attribute, 83
address attributes, 70
addressing
  otype, 80
addressing messages, methods of, 10
algorithm
  object-oriented message delivery, 77
  process-oriented message delivery, 74
allocating storage space, 145
allocation stack, 143
alt.soft-sys.tooltalk, 229
API header file, including in program, 59
application programming interface (API), 12
application programming interface (API) libraries, 30
application types, installing, 41
architecture, 13
arg_add call, 219
args attribute, 84

assigning otype, for specs, 131
attributes
address, 70, 83
arg, 84
class, 83
op, 84
scope, 70, 84
setting, 83
attributes, of message patterns, 20

B

background jobs, 17
barg_add call, 219
batch sessions, 17
broken references, 137

C

C2 qualification, 226
callback routines, 146
invoking, 123
callback routines, adding to message patterns, 95
callbacks, attached to static patterns, 125
callbacks, for handlers, 124
calls provided to manage information storage, 144
CASE Interoperability Message Sets, 6
CEPATH, 32
changing ToolTalk-enhanced shell commands, 56
checking ToolTalk databases, 18
checking ToolTalk error status, 150
class attribute, 83
close function, 202
co-edit, 18
communication process, 13
comparing objids, 134
components of the ToolTalk service, 13
computational loops, 213
connecting processes to the same session, 202
context arguments, 146
context slots, used to create environment variables, 35
contextdcl, 105, 110
contexts, defined, 27
contexts, to restrict matching, 219
convert ToolTalk type data, 30
converting ToolTalk types, script for, 155
cp command, 18
cpp command, 41
creating a ptype file, 103
creating dynamic message patterns, 95
creating general messages, 83
creating messages, 80
creating object-oriented messages, 87
creating otype files, 109
creating process-oriented messages, 86
creating specs, 131

D

database
check and recovery tool, 30
records, 13
database server
installing ToolTalk, 35
process, 13
redirecting, 37
redirecting file system partitions, 38
redirecting host machines, 37
database server redirection files, 200
database utility ttdbck, 57
databases
accessing ToolTalk, 57
check and repair utility, ttdbck, 18
displaying, checking, and repairing of ToolTalk, 57
maintaining ToolTalk, 18
debugging, with ttsnoop, 45
default session
joining, 97
quitting, 98
delete message, 90

deleting message patterns
message patterns
deleting, 96
deleting messages, 127
demonstration, 159
demostration programs
co-edit, 18
edit_demo, 18, 139
ttsample1, 18
ttsnoop, 18
des, 225
deserializing structured data, 74
Desktop Services
Started, 206
Desktop Services Message Set, 2
destroying message patterns
automatically, 96
destroying messages, 127
destroying specs, 137
determinging spec properties, 132
determining who receive messages, 10
directories, list and location of, 29
DISPLAY, 32, 201
disposition attributes, 28
Document and Media Exchange Message Set, 4
dynamic message patterns, 93
creating, 95
dynamic method, 19

E

edit_demo, 18, 139
environment variables, 31
_SUN_TT_ARG_TRACE_WIDTH, 32
_SUN_TT_FILE, 32
_SUN_TT_HOSTNAME_MAP, 32, 38
_SUN_TT_PARTIITON_MAP, 32
_SUN_TT_PARTITION_MAP, 39
_SUN_TT_SESSION, 16, 32, 65
_SUN_TT_TOKEN, 32
CEPATH, 32
created from message contexts, 35
DISPLAY, 32
SUN_TTSESSION_CMD, 32
TMPDIR, 33
TTPATH, 32
error handling functions, 150
error macros, 150
error propagation, 154
error status, 149
checking, 150
retrieving, 150
error value, 150
errors, process type, 44
event loop, 213
examining messages, 120
examining spec information, 134
examining type information, 43

F

failed connection, causes of, 36
failing requests, 127
features, of the ToolTalk service, 146
features, of ToolTalk, 8
file, 204
ToolTalk concept of, 11
file information
managing, 138
file query functions, 147
file scope, 71
file scoping, restrictions, 11
file scoping, restrictions to, 22
file-in-session scope, 73
files
hostname_map, 37
list and location of, 29
maintaining ToolTalk, 18
managing with object data, 137
object type, 107
partition_map, 38
XDR format, 14
files of interest
joining, 99

quitting, 99
file-scoped message flow, 207
file-scoped messages, queued, 226
filter routines, 147
free storage space, 90
freeing allocated storage space, 146
functions
tt_message_user, 64
functions with natural return values, 150
functions without natural return values, 150

H

handling replies easily, 120
handling requests, 125
header file, 30
help on how to invoke ttsession, 15
hostname qualification of pathnames, explicit, 228
hostname_map file, 37
how applications use ToolTalk messages, 8
how the ToolTalk technology works, 163

I

iarg_add call, 219
identifying data in existing files, 130
identifying messages easily, 119
information provided by the ToolTalk service, 143
information provided to the ToolTalk service, 143
informing sender of failed request, 127
initial session, 60
initializing your process, 61
installing application types, 41
installing the ToolTalk database server from a remote machine, 36
installing theToolTalk database server, 35
installing type information, 112
invoking callback routines, 123

J

joining default sessions, 97
joining files of interest, 99
joining multiple sessions, 98

K

kill command, 44

L

LD_LIBRARY_PATH, 201
li, 198
libtt, 14, 202, 215
libtt.a, 199
libtt.s, 199
libtt.so, 201
load balancing, 213

M

maintaining specs, 133
maintaining ToolTalk files and databases, 18
managing files that contain object data, 137
managing object and file information, 138
manpages, location of ToolTalk, 31
manually starting a session, 15
marking information for storage, 144
marking the ToolTalk API stack, 120
merging compiled ToolTalk type files into running ttsession, 112
merging type information, 112
message
delete, 90
message attributes, 69
message attributes, comparing to pattern attributes, 21
message callback, 146

message callbacks, 124
message callbacks, adding, 87
message delivery
  object-oriented algorithm, 77
  process-oriented algorithm, 74
message paterns
  unregistering, 96
message pattern attributes, 20
message patterns, 9, 19
  adding callbacks to, 95
  automatically unregistering and destroying, 96
  minimum specifications, 21
  static, 101
  updating, 97
message protocol, 12
message_status_string, 214
messages
  completing, 80
  creating, 80
  creating general-purpose, 83
  deleting, 127
  determining recipients of, 9
  examining, 120
  handling, 9
  identifying and processing easily, 119
  methods of addressing, 10
  object-oriented, 10
  observing, 9
  process-oriented, 10
  receiving, 9
  sending, 8, 90
messages, retrieving, 117
MIT X, 201
modifying applications, 160
  xedit, 160
  xfontsel, 161
modifying applications to send messages, 80
modifying makefile, 161
modifying your application to use the ToolTalk service, 12
moving objects between file systems, 136
moving objects between files, 136
multiple processes, 213
multiple sessions
  storing session ids of sessions, 98
multiple sessions, joining, 98
mv command, 18, 56

N

network types database, converting, 157
networked envirnoments, 65
news group, ToolTalk, 229
notice, 67
notifying processes if tool exits unexpectedly, 153

O

object content, 130
object data, 129
object information
  managing, 138
object specification (spec), 130
object type (otype), 107
object-oriented message delivery, 77
object-oriented messages, 10, 129
  creating, 87
objects
  moving between file systems, 136
  moving between files, 136
  ToolTalk, 130
objects, ToolTalk, 228
objid
  comparing, 134
  obtaining, 131
  obtaining new, 133
  retrieving new, 133
obtaining new objid, 133
obtaining objid, 131
op attribute, 84
otype
  assigning for specs, 131
otype addressing, 80

otype file, 107
otype files
creating, 109
header information, 109
signature information, 110
otype files, installing, 41
otype signature, 108
otypes, examining information, 43

P

partition_map file, 38
pattern attributes, comparing to message attributes, 21
pattern callback, 146
pattern callbacks, 124
pointers, to API objects, 146
point-to-point (PTP) message passing feature, 83
point-to-point messages, 124
process
communication, 13
database server, 13
process identifier (procid), 61
process type (ptype), 101
process type errors, 44
process type, declaring, 113
processing messages easily, 119
process-oriented message delivery, 74
process-oriented messages, 10
creating, 86
procid, 61, 204
closing default, 65
setting default, 61
Project DOE, 198
ps command, 44
ptype, 204
ptype file, creating, 161
ptype files
creating, 103
property information, 104
registering, 102
registering with ToolTalk, 113
signature information, 105
unregistering with ToolTalk, 115
ptype files, installing, 41
ptype signature, 102
ptype, installing, 162
ptypes, check for existing, 112
ptypes, examining information, 43
ptypes, multiple, 115
ptypes, undeclaring, 115

Q

quitting default session, 98
quitting files of interest, 99

R

read in the types from database, 16
reading
hostname_map files, 38
partition_map files, 39
reading ToolTalk data from read-only file system partitions, 37
read-only file systems, 130
read-only files, creating objects of pieces of, 130
realpath, 228
receiving ToolTalk messages, 9
recipients, 8
recognizing replies easily, 120
records database, 13
redirecting file system partitions, 38
redirecting host machines, 37
redirecting the ToolTalk database server, 37
register file scope patterns, 204
registering
in a specified session, 62
in the initial session, 61
with the ToolTalk service, 60
registering in multiple sessions, 63
registering ptypes, 102

rejecting requests, 127
removing type information, 43
repairing ToolTalk databases, 18
replies
  recognizing and handling easily, 120
replying to requests, 125
request, 67
requests
  failing, 127
  handling, 125
  informing sender of failed, 127
  rejecting, 127
  replying to, 125
reread types file, 16
rereading type information, 44
retrieving new obji, 90
retrieving new objid, 133
retrieving ToolTalk error status, 150
return value
  natural, 150
  no natural, 150
returned integer, status, 152
returned pointer, status, 151
returned value, status, 150
reverting to previous versions of the ToolTalk database, 37
rm command, 18, 57
routines
  callback, 146
  filter, 147
rpc.ttdbserverd, 13, 130, 198
running the new ToolTalk database server, 37
runtime stack, 143

S

same process, sending and receiving messages in, 64
scenarios illustrating the ToolTalk service in use, 2
scope attribute, 84
scope attributes, 70
  file, 71
  file-in-session, 73
  session, 73
scope, to union of TT_FILE_IN_SESSION and TT_SESSION, 71
scopes, that use files, 71
scopes, types of, 22
scoping messages to every client with registered interest, 73
scoping to file in session, 24
scoping to file only, 23
scoping to files and sessions, 25
scoping to session only, 22
senders, 8
sending messages, 90
  modifying applications, 80
sending notices, 67
sending requests, 68
sending ToolTalk messages, 8
serializing structured data, 74
server authentication level, 15
session identifier (sessid), 11
session identifiers, multiple for one session, 15
session scope, 73
session, ToolTalk concept of, 10
sessions bound to a character terminal, 17
session-scoped message flow, 206
session-scoped messages, queued, 226
setting attributes, 83
setting up to receive messages, 63
share/include/desktop, 198
shell commands
  standard
    cp, 18
    mv, 18, 56
    rm, 18, 57
  ToolTalk-enhanced, 18, 29, 56, 138
    changing, 56
    ttmv, 56
shell commands, ToolTalk-enhanced

ttcp, 56, 138
ttmv, 56, 138
ttrm, 56, 138
ttrmdir, 56, 138
tttar, 56, 138
shell scripts
ttrsh, 33
signals, to which ttsession responds, 16
signatures
otype, 108
ptype, 102
SIGUSR1 signal, 16
SIGUSR2 signal, 16
silent operation, 15
spec *See object specification*
spec, destroying an object, 137
specs
adding values to properties, 132
assigning otype, 131
creating, 131
destroying, 137
determining properties, 132
examining information, 134
maintaining, 133
moving objects, 136
querying for objects, 134
storing properties, 132
updating, 133
updating existing properties, 132
writing into ToolTalk database, 132
start a process tree session, 16
start process tree sessions, 16
starting a session manually, 15
starting a ToolTalk session, 15
starting programs on remote hosts, 33
state change messages, 69
static message patterns, 101
static method, 19
static patterns
adding callbacks, 89
attaching callbacks, 125
storing
hostname_map files, 38
partition_map files, 38
storing spec properties, 132
_SUN_TT_SESSION, 16
SUN_TT_SESSION, 203
SUN_TTSESSION_CMD, 32
switching between multiple sessions, 205
system types database, converting, 156

T

-t option, 206
-t option, of ttsnoop, 45
TMPDIR environment variable, 33
ToolTalk database server
reverting to previous versions, 37
running new, 37
ToolTalk message sets
Desktop, 2
Document and Media Exchange, 4
ToolTalk messages, 8
ToolTalk object, 130
ToolTalk service, 1
ToolTalk type compiler tt_type_comp, 107
ToolTalk types databases, moving, 158
ToolTalk-enhanced shell commands, 138
trace mode, 16, 206, 217, 226
trace mode, toggling, 16
TT_BOTH, 25
tt_c.h, 199
TT_CALLBACK_CONTINUE, 208
TT_CALLBACK_PROCESSED, 208
tt_close, 65, 96, 202
tt_default_file, 228
tt_default_session_set, 62, 204
tt_fd, 61, 62
TT_FILE, 23
TT_FILE_IN_SESSION, 24
tt_file_join, 99
tt_file_objects_query, 134, 147
tt_file_quit, 99
TT_HANDLED, 118

tt_int_error, 152
tt_is_err, 151, 152
tt_message__set, 83
tt_message_accept, 120, 216
tt_message_callback_add, 87, 120, 211
tt_message_create, 83
tt_message_destroy, 87, 90, 127
tt_message_fail, 127
tt_message_file, 72, 228
tt_message_file attribute, 212
tt_message_file_set, 73
tt_message_object, 90, 133
tt_message_receive, 117, 124, 208, 213, 214
tt_message_reject, 127, 213, 216
tt_message_send, 137
tt_message_send_on_exit, 153
tt_message_status_set, 127
tt_message_status_string_set, 127
tt_message_user call, 209
tt_message_user_set, 120
tt_objid_equal, 134
tt_onotice_create, 87
tt_open, 61, 62, 199, 217
tt_orequest_create, 87
tt_pattern_add, 95
tt_pattern_callback_add, 95, 119
tt_pattern_create, 95
tt_pattern_destroy, 96
tt_pattern_register, 96
tt_pattern_set, 95
tt_pattern_unregister, 96, 113, 214
tt_pnotice_create, 86
tt_pointer_error, 151
tt_prequest_create, 86
tt_ptype_declare, 113
tt_ptype_undeclare, 113, 115
TT_SESSION, 22
tt_session_join, 97
tt_session_quit, 98
tt_spec_bprop, 134
tt_spec_create, 131
tt_spec_destroy, 137
tt_spec_file, 134
tt_spec_move, 136
tt_spec_prop, 134
tt_spec_prop_add, 132
tt_spec_prop_set, 132
tt_spec_type, 134
tt_spec_type_set, 131
tt_spec_write, 132
Tt_status, 65
tt_status_message, 151
tt_type_comp, 41, 102, 107, 199
TT_WRN_STALE_OBJID, 90
TT_WRN_START_MESSAGE, 120, 216
ttce2xdr, 199
ttce2xdr script, 155
ttcp, 56, 138, 198
ttdbck, 57, 199
ttdbck utility, 18
ttm, 198
ttmv, 56, 138
ttmv command, 56, 228
TTPATH, 32, 200
ttrm, 56, 138
ttrmdir, 56, 138, 198
ttrsh shell script, 33
ttsample1, 18
ttsession, 13, 29, 198
ttsession parameters, 15
ttsnoop, 18
ttsnoop utility, 206
ttsnoop, debugging with, 45
ttta, 198
tttar, 56, 138
type compiler, 30
type compiler tt_type_comp, 102
type information
    examining, 43
    examining all types, 43

installing, 112
merging, 112
reading, 44
removing, 43
types file, rereading, 16
types of scopes, 22

U

unix, 225
unregistering a message pattern, 96
unregistering message patterns automatically, 96
update existing spec properties, 132
updating existing specs, 133
updating message patterns, 97
updating the ToolTalk service, 44
user data cells, 211
user type database, converting, 155
USR1 signal, 206

V

-v option, 31
version number, 16
version string, 31

W

wildcarding patterns, 218
writing specs, into ToolTalk database, 132
writing ToolTalk data to read-only file system partitions, 37

X

X Window System, establishing a session under, 17
xauth, 225
XDR format file, 14
Xedit, 159
Xfontsel, 159
XtAppAddInput call, 208