NAME

oclock – display time of day

SYNOPSIS

oclock [*-options...*]

DESCRIPTION

Oclock simply displays the current time on an analog display

OPTIONS

-fg *foreground color*
: choose a different color for the both hands and the jewel of the clock

-bg *background color*
: choose a different color for the background.

-jewel *jewel color*
: choose a different color for the jewel on the clock.

-minute *minute color*
: choose a different color for the minute hand of the clock.

-hour *hour color*
: choose a different color for the hour hand of the clock.

-backing WhenMapped | Always | NotUseful
: selects an appropriate level of backing store.

-geometry *geometry*
: define the initial window geometry; see **X11**(7).

-display *display*
: specify the display to use; see **X11**(7).

-bd *border color*
: choose a different color for the window border.

-bw *border width*
: choose a different width for the window border. As the Clock widget changes its border around quite a bit, this is most usefully set to zero.

-noshape
: causes the clock to not reshape itself and ancestors to exactly fit the outline of the clock.

-transparent
: causes the clock to consist only of the jewel, the hands, and the border.

COLORS

If you would like your clock to be viewable in color, include the following in the #ifdef COLOR section you read with xrdb:

∗customization: -color

This will cause oclock to pick up the colors in the app-defaults color customization file: **/usr/openwin/lib/app-defaults/Clock-color**. Below are the default colors:

Clock∗Background: grey

Clock*BorderColor: light blue
Clock*hour: yellow
Clock*jewel: yellow
Clock*minute: yellow

SEE ALSO

X11(7), X Toolkit documentation

COPYRIGHT

AUTHOR

Keith Packard, MIT X Consortium