NAME

PEXEncodedAnnoText – Encoded 3D Annotation Text Primitive

SYNTAX

void PEXEncodedAnnoText(Display **display*, XID *resource_id*, PEXOCRequestType *req_type*, PEXCoord **origin*, PEXCoord **offset*, unsigned int *count*, PEXEncodedTextData **encoded_text*)

PARAMETERS

display	A pointer to a display structure returned by a successful **XOpenDisplay** call.
resource_id	The resource identifier of the renderer or structure.
req_type	The request type for the output command (**PEXOCRender, PEXOCStore, PEXOCRenderSingle** or **PEXOCStoreSingle**).
origin	The origin of the text string.
offset	The relative position of the text string from the origin.
count	The number of encoded text strings.
encoded_text	An array of encoded text strings.

RETURNS

None

DESCRIPTION

This function creates an annotation text output primitive.

This function is similar to **PEXAnnotationText**(3)**,** except that multiple encoded text strings are specified. Each text string in the encoded text array has a character set, a character set width, an encoding state, and a list of characters.

The character set is an index into the current font group. Font groups contain individual fonts which are numbered starting at one; a value of three selects the third font in the font group currently being used. If a character set is not available in the current font group then the entire string will be rendered using the default font group. If a character set value is not available in the default font group then that portion of the string will be rendered in an implementation-dependent manner. The character set width indicates the width or size of characters in the strings. Valid values for character set width are **PEXCSByte, PEXCSShort** and **PEXCSLong.** The encoding state is provided for use by the application and is not interpreted by the PEX server.

All other aspects of this primitive are the same as **PEXAnnotationText**(3)**.**

DATA STRUCTURES

```
typedef struct {
        unsigned short      character_set;
        unsigned char       character_set_width;    /* PEXCSByte, PEXCSShort,
                                                       PEXCSLong */
        unsigned char       encoding_state;
        unsigned short      reserved;
        unsigned short      length;
        char                *ch;
} PEXEncodedTextData;
```

See also **PEXlib.h.**

ERRORS

BadPEXRenderer
The specified renderer resource identifier is invalid.

BadPEXStructure
The specified structure resource identifier is invalid.

SEE ALSO

PEXSetTextFontIndex(3)
PEXSetTextPrecision(3)
PEXSetCharExpansion(3)
PEXSetCharSpacing(3)
PEXSetTextColorIndex(3)
PEXSetTextColor(3)
PEXSetATextHeight(3)
PEXSetATextUpVector(3)
PEXSetATextPath(3)
PEXSetATextAlignment(3)
PEXSetATextStyle(3)
PEXSetTextBundleIndex(3)